See discussions, stats, and author profiles for this publication at: https://www.researchgate.net/publication/317008117

St. Marys Flood Resiliency Project

Technical Report · May 2017

CITATIONS		READS	
0		302	
7 author	s, including:		
1-C	Jill Gambill		Chas Hopkinson
	University of Georgia	C EV	University of Georgia
	6 PUBLICATIONS 16 CITATIONS		160 PUBLICATIONS 10,410 CITATIONS
	SEE PROFILE		SEE PROFILE
10-1	Jason M. Evans		
AL .	Stetson University		
	87 PUBLICATIONS 983 CITATIONS		
	SEE PROFILE		
Some of	the authors of this publication are also working on these related projects:		

long-term ecological research View project

Estuarine biogeochemistry View project

St. Marys Flood Resiliency Project

Funded by the National Sea Grant Program

Administered by the National Oceanic and Atmospheric Administration (NOAA), Sea Grant conducts research, outreach and education in 33 coastal and Great Lakes states.

FINAL REPORT MAY 2017





Marine Extension and Georgia Sea Grant UNIVERSITY OF GEORGIA







Carl Vinson Institute of Government UNIVERSITY OF GEORGIA





Lamar Dodd School of Art UNIVERSITY OF GEORGIA



ST. MARYS FLOOD RESILIENCY PROJECT

FINAL REPORT May 2017

Authors: Jill Gambill, Madeleine Russell, Kelly Spratt, Jessica Whitehead, Mariana Alfonso, Charles S. Hopkinson, Jason M. Evans

FUNDED BY THE NATIONAL SEA GRANT COLLEGE PROGRAM

Administered by the National Oceanic and Atmospheric Administration (NOAA), Sea Grant conducts research, outreach and education in 33 coastal and Great Lakes states.

Executive Summary

Since 2013, the City of St. Marys has collaborated with Georgia Sea Grant, the University of Georgia, Stetson University and North Carolina Sea Grant to engage in flood resiliency planning. The historic, low-lying community has already experienced approximately nine inches of sea-level rise since 1897, and this trend is expected to accelerate in the future. This project has paired local knowledge with academic expertise to analyze risks to the City's infrastructure and provide initial recommendations to manage flooding risks over the next 50 years. A model for other communities, this effort has grown to include other cities and counties throughout the U.S. southeast Atlantic region.

Participatory Research to Identify and Mitigate Flood Hazards

The project began with a series of stakeholder interviews, town hall public meetings and facilitated discussion sessions that documented local knowledge about flood hazards in St. Marys. This participatory engagement process was based upon the Vulnerability,



Consequences and Adaptation Planning Scenarios (VCAPS) structural modeling approach. Results from the VCAPS process were then used to inform a series of custom geo-spatial vulnerability assessments that analyzed current and future flood risks to property and infrastructure under different sea-level rise scenarios.

The vCAPS process and geo-spatial assessments both indicated the high vulnerability of historic downtown St. Marys, which is located along the banks of the St. Marys River estuary, to current and future coastal flooding. While the most serious and acute flood risks in St. Marys are associated with storm surges from tropical cyclones, there are increasing concerns about more chronic flood events associated with intense rain storms that occur at or near high tide. Detailed analysis of the City's infrastructure indicates that the configuration of the stormwater drainage system, which was built many decades ago without any knowledge of long-term sea-level rise, is a major source of flood vulnerability. This vulnerability is expected to worsen as a direct function of sea-level rise unless the local stormwater infrastructure system is upgraded over time. Although there are substantial challenges, much of St. Marys flood vulnerability likely can be managed with appropriate planning and investments over the next several decades.

Community Rating System

A complementary objective of this project was for Georgia Sea Grant personnel to assist the City of St. Marys with its application to join the Federal Emergency Management Agency's (FEMA) Community Rating System (CRS). CRS is a voluntary FEMA program that rewards communities for exceeding minimum floodplain management standards, thereby improving public safety and economic stability within the community.

On May 1, 2016, St. Marys successfully joined CRS with a Class 7 score. This translates into a 15 percent reduction in National Flood Insurance Program premiums for properties located within the Special Flood Hazard Area. In the first year following this successful CRS application, it is estimated that City residents saved over \$87,000 on their flood insurance premiums.

The unique model of Sea Grant personnel providing CRS assistance to a local government resulted in several outcomes of local, regional and national interest.

- Documentation of public processes that educate and engage the public about the hazards of flooding, storm surge and sea-level rise can be used to strengthen a community's CRS application.
- The City of St. Marys and Camden County joined the Coastal Georgia CRS Users Group, an innovative partnership that allows for local governments and their floodplain managers to share best practices and lessons learned that strengthen local flood resiliency.
- The floodplain managers of Camden County and St. Marys have collaborated to create the state's first Program for Public Information (PPI), an outreach program designed to increase local awareness of flooding and coastal hazards.
- Georgia Sea Grant collaborated with the City of St. Marys staff and Georgia Department of Natural Resources (DNR) to document and calculate the amount of open space within the city boundaries. CRS points are awarded for the amount of **open space** areas that are preserved, or in the process of becoming preserved, to their natural state.
- The City of adopted an ordinance requiring that all new construction have two feet of freeboard. Freeboard is elevating the lowest floor of a building, in this case houses, by a set additional height above the National Flood Insurance Program's minimum height requirements. This freeboard requirement provides added margins of safety that can be expected to reduce damage to structures in the event of future flooding events.





CHAPTER 1: Introduction

The southeastern U.S. Atlantic coast is highly vulnerable to climate-related stressors, such as hurricanes, extreme rainfall, extreme drought and sea-level rise. This region has also experienced exceptional growth in both population and the built environment over the past several decades and is expected to continue growing above the pace of other U.S. regions for the foreseeable future. Without appropriate planning for coastal hazards, an increasing number of people, property, infrastructure and natural systems in southeast U.S. coastal communities are likely to become vulnerable to climate-related risks.¹

An increasing body of scientific knowledge and local observations indicate that sealevel rise is already impacting U.S. communities. Some of the most visible effects include flooding of low-lying roads during high tide events, inland movement of saltwater ecosystems and increased erosion and flooding of waterfront areas during storm events. As these impacts and changes occur, more local governments within the coastal zone are initiating long-term resilience planning programs to help their communities better adapt to current and future conditions.²

AN INNOVATIVE PARTNERSHIP

In 2013, St. Marys was selected through a nationwide grant competition as one of five locations in the United States to undergo community resilience and adaptation planning. Funded by National Oceanic and Atmospheric Administration's (NOAA) National Sea Grant Program, the overall project was designed to assess and make initial recommendations for addressing local vulnerability to coastal flooding and sea-level rise over a 50-year horizon. Formal partners in this project included the City of St. Marys, Georgia Sea Grant, the University of Georgia, Stetson University and North Carolina Sea Grant. Additional technical assistance and collaboration was also provided by the St. Marys EarthKeepers, Camden County, Georgia Department of Natural Resources, Coastal Regional Commission of Georgia and Ecological Planning Group, LLC. Students and faculty from the University of Georgia's Lamar Dodd School of Art and the College of Environment and Design also contributed to project outreach and implementation.

Conversations forming this collaboration began in February 2013, when the St. Marys EarthKeepers organized a public seminar on local vulnerabilities to sea-level rise. This event featured speakers from Georgia Sea Grant and attracted approximately 100 members of the local community, including several elected officials and local government staff. From these initial discussions, the St. Marys EarthKeepers built bridges between City government and Georgia Sea Grant researchers to develop this project's focus, methodology and goals.

The methods for the St. Marys project were partially modeled after an ongoing sea-level rise adaptation project implemented by Georgia Sea Grant in the City of Tybee Island.³ However, discussions with personnel from North Carolina Sea Grant indicated the potential for synergies in expertise among the two Sea Grant programs if a collaborative project was developed and implemented in communities within both states. Accordingly, the overall project was designed to include concurrent development of a flood resilience planning process in Hyde County, North Carolina, using similar methods as those utilized in St. Marys. Under this project design, North Carolina Sea Grant researchers led the implementation of stakeholder engagement through the Vulnerabilities, Consequences and Adaptations Planning Scenario (VCAPS) process, while Georgia Sea Grant researchers researchers provided geo-spatial modeling of flood hazards. Both Sea Grant programs collaborated to provide targeted assistance to the local governments for the purpose of improving Community Rating System (CRS) scores, thereby enhancing flood resilience and lowering local flood insurance premiums as set by the National Flood Insurance Program (NFIP).



The St. Marys EarthKeepers built bridges between City government and Georgia Sea Grant researchers to develop this project's focus, methodology and goals.

A RESILIENT ST. MARYS

In the context of local planning, **resilience** means the ability of a community to absorb or bounce back from a natural or man-made event with minimal impact and damage. This planning effort investigated how to make St. Marys more resilient to the climate-related hazards of flooding, storm surge and sea-level rise.

Planning for coastal hazards is necessary in order to:

- Ensure the safety of residents and visitors
- Reduce the loss of property
- Maintain the quality of life
- Protect the history of the community
- Decrease disruption of commerce
- Aid decision-making, such as prioritizing, budgeting, investment and development
- Minimize threats to public health

DEFINITIONS:

Hazard: Natural or man-made event with potential to damage communities, ecosystems, buildings and infrastructure. Vulnerability: Resources at risk from the damaging effects of a natural or man-made disaster.

Resilience: Ability to bounce back from or cope with a hazard event with minimum impact and damage.

Adaptation: Actions taken to help communities avoid, manage or reduce consequences of actual or expected hazards.

REPORT OVERVIEW

Following this introduction, the remainder of this report is organized into five chapters. Chapter 2 provides a general overview St. Marys' vulnerability to flooding and sea-level rise, describing drivers and trends of hydrological changes and coastal hazards affecting the community. Chapter 3, *Community Outreach and Engagement*, provides a specific history of the public participation processes used to inform the planning effort in St. Marys. This includes an analysis of stressors, impacts, barriers and innovative strategies to address flooding in St. Marys. Chapter 4, *Cost-Benefit Assessment of Adaptation Options*, describes flood risk calculations and associated benefit-cost analyses of potential adaptation actions. Chapter 5, *Community Rating System*, concludes the report by describing efforts in St. Marys and other coastal Georgia communities to reduce flood insurance rates through participation in FEMA's Community Rating System.



- 1 Hauer, M. E., J. M. Evans, and D. R. Mishra. 2016. Millions projected to be at risk from sea-level rise in the continental United States. Nature Climate Change DOI:10:10.1038/nclimate2961.
- 2 Nicholls, R.J. 2011. Planning for the impacts of sea level rise. Oceanography 24:142–155. Hinkell, J., D. Lincke, A.T. Vafeidas, M. Perrette, R.J. Nicholls, R.S.J. Tol, B. Marzeon, X. Fettweis, C. Ionescu, and A. Levermann. 2014. Coastal flood damage and adaptation costs under 21st century sea-level rise. PNAS 111:3292–3297.
- 3 Evans, J. M., J. Gambill, R. J. McDowell, P. W. Prichard, and C. S. Hopkinson. 2016. Tybee Island Sea-Level Rise Adaptation Plan. Athens: Georgia Sea Grant. DOI: 10.13140/RG.2.1.3825.9604/1.

Coastal Hazards in St. Marys

St. Marys, located in Camden County, is coastal Georgia's southernmost city (FIGURE 2.1). Separated from Florida by the St. Marys River, initial settlement of St. Marys began in 1787 and the City was incorporated in 1802. The community is home to valuable historical assets, including antebellum homes, churches, cemeteries and other important sites that span over two centuries of American history.

As of the 2010 U.S. Census, the City of St. Marys covered an area of roughly 22.51 square miles and was home to approximately 18,000 residents. St. Marys is perhaps best known as the gateway to Cumberland Island, Georgia's largest and southernmost barrier island. Designated by Congress in 1972 as a national seashore, most of Cumberland Island is owned and managed by the National Park Service. A passenger ferry to Cumberland Island departs from downtown St. Marys, which contributes to the City's popularity as a tourist destination. St. Marys is also located adjacent to the Kings Bay Naval Submarine Base.



FLOODING IN ST. MARYS

Records from the NOAA tide gauge at Fernandina Beach, FL, located just a few miles south of St. Marys, show a daily tide range of approximately 6.6 feet. During full moon spring tide cycles, the tide range can increase to almost 9 feet between high and low tides. While these relatively large tidal amplitudes help to support the very extensive and highly productive marshlands found throughout coastal Georgia, they can also bring about enhanced flood risks when major rainfall or storm surge events co-occur with a high tide cycle.

St. Marys is vulnerable to three types of flooding: coastal flooding, shallow flooding and riverine flooding from the St. Marys River. Coastal flooding includes storm surge and saltwater inundation from extreme high tides. Shallow flooding occurs mostly in the spring and summer and is due to heavy rainfalls that cannot be effectively drained by the local stormwater infrastructure. Strong



FIGURE 2.1: OVERVIEW MAP OF ST. MARYS, GA

easterly winds and high tides can increase the severity of shallow flooding, as high waters in the tidal St. Marys River effectively reduce the stormwater drainage potential. Riverine floods are associated with large amounts of rainfall throughout the entire St. Marys River watershed, which extends upstream to the eastern portions of the Okefenokee Swamp, that eventually drain downstream through the lower St. Marys River. Due to these flood risks, approximately 62% of St. Marys is designated as a Special Flood Hazard Area by the Federal Emergency Management Agency (FEMA).⁴ Figure 2.2 provides a visual representation of the amount of the City's land located within and outside of the FEMA designated floodplain.

Approximately 62% of St. Marys is designated as a Special Flood Hazard Area by the Federal Emergency Management Agency (FEMA).

Although these hazards are an inherent feature of the coastal zone, the high quality of life and natural beauty of Georgia's coastal region is attracting more and more people from around the country. Coastal Georgia experienced an 82 percent increase in population from 1960–2010,⁵ while St. Marys specifically experienced a 21.2 percent population increase 2000 to 2014.⁶ ⁷Looking forward, this trend appears to be accelerating. For example, a recent study projects a 62 percent population growth in the state's six coastal counties by 2050 and further suggests that sea-level rise would put approximately 93,000 to 178,000 people in coastal Georgia at risk of daily tidal flooding impacts by 2100.⁸



FIGURE 2.2: FEMA FLOODPLAIN CATEGO-RIES IN THE CITY OF ST. MARYS. THE FEMA BASE FLOOD ELEVATION (BFE) HEIGHTS ARE IN FEET ABOVE THE NORTH AMERICAN VERTICAL DATUM OF 1988 (NAVD88).

HURRICANES AND STORM SURGES

Storm surge is defined by the National Hurricane Center as "an abnormal rise in sea level accompanying a hurricane or other intense storm."⁹ It is well understood that much of coastal Georgia and broader southeast United States is highly vulnerable to coastal flooding, both from extreme rainfall events and tidal storm surges.¹⁰ Much of this vulnerability is due to the region's low coastal elevations, as shallow water tables and very low slopes within the landscape prevent rapid drainage in the event of large rainfall events. Additional factors such as the concave configuration of the Georgia bight, the very large and shallow coastal shelf and high local tidal amplitude also create the potential for very large storm surges within coastal Georgia. Storm surges in excess of 30 feet above normal tidal levels, which could in some areas travel up to 30 miles inland, are possible in the case of an extremely large and powerful hurricane making a direct landfall along the Georgia coast.¹¹

The relative infrequency of hurricane strikes in coastal Georgia since the beginning of the 20th century has led to some public perception that the region is unlikely to experience major hurricane impacts.¹² It is important to stress that historical records do not support this perception, as it is well-documented that coastal Georgia experienced at least six direct hits from major hurricanes during the 19th century.¹³ Several of these 19th century storms produced large and destructive storm surges, resulting in many destroyed buildings, severely damaged agricultural fields and major loss of human life. Geologic records further show that the Georgia coast has been regularly impacted by large hurricanes over the past several thousand years.¹⁴

On October 7, 2016, the passing of Hurricane Matthew just off coastalal Georgia resulted in significant coastal flooding and wind damage within St. Marys. Fortunately, Hurricane Matthew did not make direct landfall near St. Marys, and the peak storm surge did not correspond with a high tide, both of which mitigated the storm's flood effects within the City. Nevertheless, the nearby NOAA tide gauge at Fernandina Beach, FL, recorded a peak tide level of 6.91 feet (NAVD88), or 4.17 feet above mean higher high water (MHHW; the height of an average daily high tide), during Hurricane Matthew. This storm surge was

the second highest water level recorded at Fernandina Beach since the tide gauge was originally installed in 1897. The only larger storm surge event within the local tide gauge record was associated with a large hurricane that made a direct strike at Cumberland Island on October 2, 1898. This 1898 storm produced a peak water level of 9.65 feet (NAVD88), or 6.91 feet above MHHW, at Fernandina Beach. Other storm surge events of note within the Fernandina Beach tide gauge record include the 1944 Cuba-Florida hurricane (peak water level of 6.48 feet above NAVD88 on October 19, 1944), Hurricane Dora (peak water level of 6.68 feet above NAVD88 on September 9, 1964) and Hurricane Frances (peak water level of 5.50 feet above NAVD88 on September 27, 2004).¹⁵

The Georgia Bight and high local tidal amplitude create the potential for very large storm surges within coastal Georgia.

SEA-LEVEL RISE

The full dataset record from the Fernandina Beach tide gauge indicates a long-term sealevel rise of approximately nine inches since 1897. This amounts to a local trend of about 8.1 inches in sea-level rise over the course of a 100-year period (Figure 2.3). This sea-level rise trend is expected to accelerate over the next several decades. Recent NOAA projections suggest a minimum sea-level rise of eight inches by the year 2100 if global efforts to reduce greenhouse gases prove effective and climate sensitivity is low. However, up to 6.6 feet of sea-level rise by 2100 is possible if polar ice caps begin a large-scale melt event similar to those observed at the end of the last ice age.¹⁶ Many scientists and planners in coastal Georgia suggest that local governments should prepare for a scenario of approximately 3.3 feet of sea-level rise by 2100.¹⁷ Figure 2.4 summarizes the range of sea-level rise scenarios through 2100 as projected by NOAA.

NOAA scientists have found that sea-level rise is increasing the amount of "nuisance" or "sunny-day" tidal flooding events that are occurring in coastal communities across the United States.¹⁸ Such nuisance floods occur during regular high tide events and are not associated with major rainfall events or storm surges. Direct impacts of these nuisance flood events can include tidal infiltration into wastewater systems, saltwater flooding of roads and yards and temporary economic disruption within affected communities. Extreme high tide events also are known to infiltrate into stormwater infrastructure systems, resulting in loss of drainage capacity that can result in further flooding with the co-occurrence of even moderate rainfall events (Figure 2.5).



Sea Level Rise at Fernandina Beach, FL TIDE GAUGE DATA 1897–2015

FIGURE 2.3



FIGURE 2.4: BOX ON SEA-LEVELS AND GLOBAL CLIMATE CHANGE

At the Fernandina Beach tide gauge, NOAA has defined the nuisance flooding threshold as an event exceeding 4.68 feet above NAVD88 (1.94 feet above MHHW). In 2015, a total of seven nuisance flooding events were observed at the Fernandina Beach tide gauge, which was the highest amount for any year on record since the installation of the tide gauge in 1897. Many other tide gauges throughout the southeast United States also showed a record amount of nuisance flood events in 2015. It is generally believed that long-term sea-level rise combined with the occurrence of strong El Nino climate conditions were responsible for the increased number of nuisance flood events observed at Fernandina Beach and other tide gauges in 2015.¹⁹

In addition to the frequency and severity of nuisance tidal flooding, sea-level rise has the effect of increasing the height of storm surges. For example, the storm surge experienced as an effect of Hurricane Matthew was at least eight inches higher than would have occurred as a result of a similar storm affecting St. Marys approximately 100 years ago. To put another way, without sea-level rise, the storm surge from Hurricane Matthew would have been somewhat lower than what was experienced from Hurricane Dora in 1964, instead of a few inches higher. These differences in water height can translate into significant differences in the extent and amount of flood damages experienced by affected homes and businesses.

Fully Operating System	Stage 1: Salt Water Plug
Stage 2: Fresh Water Flooding After Precipi-	Stage 3: Salt Water Flooding
Ground Sky Fresh Water Salt Water	Stormwater Drainage Infrastructure

FIGURE 2.5: STAGES OF STORMWATER DRAINAGE FAILURE DUE TO SEA-LEVEL RISE. GRAPHIC BY EMILY NIEDERMAN, STETSON UNIVERSITY.

⁴ FEMA. 2007. Flood Insurance Study, Camden County, Georgia and Incorporated Areas. Flood Insurance Study Number 13039CV000A Federal Emergency Management Agency. http://www.georgiadfirm.com/pdf/panels/13039cv000a.pdf.

⁵ NOAA, National Coastal Population Report, Population Trends from 1970 to 2020, 7 (2012). http://oceanservice.noaa.gov/facts/ coastal-population-report.pdf.

⁶ U.S. Census Bureau, Population Estimates Program (PEP), Updated annually. http://www.census.gov/popest/. U.S. Census Bureau, 2010 Census of Population, P94–171 Redistricting Data File. Updated every 10 years. http://factfinder.census.gov.

⁷ Census Viewer. http://censusviewer.com/city/GA/Saint%20Marys.

⁸ Hauer, M., J. Evans, and C. Alexander. 2015. Sea-level rise and sub-county population projections in coastal Georgia. Population & Environment 37:44–62.

⁹ GEMA. 2015. The Official Georgia Hurricane Guide. Atlanta: Georgia Emergency Management Agency. http://www.weather.gov/media/ chs/misc/GAHurricaneGuide.pdf.

¹⁰ Carter, L. M., J. W. Jones, L. Berry, V. Burkett, J. F. Murley, J. Obeysekera, P. J. Schramm, and D. Wear. 2014. Ch. 17: Southeast and the Caribbean. Climate Change Impacts in the United States: The Third National Climate Assessment, J. M. Melillo, Terese (T.C.) Richmond, and G. W. Yohe, Eds., U.S. Global Change Research Program, 396–417.

¹¹ Supra note 9.

¹² Pavey, R. 2010. Georgia rarely gets hit by hurricanes: here's why. The Augusta Chronicle. September 1. http://chronicle.augusta.com/ content/blog-post/rob-pavey/2010-09-01/georgia-rarely-gets-hit-hurricanes-here-s-why.

¹³ Fraser, W. J. 2006. Lowcountry Hurricanes: Three Centuries of Storms at Sea and Ashore. Athens: University of Georgia Press.

¹⁴ Kiage, L. M., D. Deocampo, T. A. Mccloskey, T. A. Bianchette, and M. Hursey. 2011. A 1900-year Paleohurricane Record from Wassaw Island, Georgia, USA. Journal of Quarternary Science 26:714–722.

¹⁵ NOAA. 2016. Fernandina Beach, FL - Station ID: 8720030. http://co-ops.nos.noaa.gov/stationhome.html?id=8720030.

¹⁶ Parris, A., P. Bromirski, V. Burkett, D. Cayan, M. Culver, J. Hall, R. Horton, K. Knuuti, R. Moss, J. Obeysekera, A. Sallenger, and J. Weiss. 2012. Global Sea Level Rise Scenarios for the US National Climate Assessment. NOAA Tech Memo OAR CPO-1. 37 pp.

¹⁷ Supra note 8.

¹⁸ Sweet, W.V. and J. J. Marra. 2016. 2015 State of U.S. "Nuisance" Tidal Flooding. https://www.ncdc.noaa.gov/monitoring-content/ sotc/national/2016/may/sweet-marra-nuisance-flooding-2015.pdf.

¹⁹ Ibid

CHAPTER 3:

Initial conversations that led to this planning effort took place during a two-hour seminar and public discussion about the City's vulnerability to sea-level rise, hosted by the St. Marys EarthKeepers, on February 28, 2013. Faculty and staff from Georgia Sea Grant gave a series of presentations about sea-level rise science in the context of the Georgia coast, as well as preliminary hazard and vulnerability analyses specific to infrastructure and property in St. Marys. These analyses were tailored to a range of sea-level rise sciencies that could be reasonably expected over the next 30 years. The presentations were followed by an open-ended audience question and answer period.

The St. Marys Flood Resiliency Project began with a participatory framework previously implemented in Tybee Island and other southeastern communities planning for flood hazards. The project endeavored to capture local, first-hand perspectives on the challenges and opportunities of addressing coastal hazards. This entailed partnering with the City and community as equal participants in the research and planning process. The planning process also utilized multidisciplinary perspectives in order to approach research and public engagement efforts from diverse viewpoints.

PUBLIC INPUT

A key component of the project was extensive public input that included in-depth interviews, a town hall meeting, extensive conversations with city department leaders and a two-day brainstorming meetings with a stakeholder advisory committee. The interviews and public meetings helped to locate places that are vulnerable to flooding. The facilitated discussions further identified which vulnerable assets are most valued or critical to the community's wellbeing and potential adaptation actions to explore.

To better understand the opportunities and challenges of resilience planning in St. Marys, the project team gathered feedback and on-the-ground insights from constituents, elected officials and community leaders. A series of 20 in-depth interviews were conducted with government officials and other knowledgeable members of the St. Marys community from February–March 2014. These interviews aimed to capture common local concerns and observations associated with flooding and other climate hazards. Following this interview process, the project team hosted a public Town Hall meeting on March 19, 2014, to collect additional input on local vulnerabilities.



Many residents expressed that nor'easters are more of a concern than hurricanes, as well as beliefs that the city is fairly protected from hurricanes by the Georgia Bight. Formal stakeholder discussion sessions were conducted over the course of two days (March 20–21, 2014) with public officials and members of the community known to have extensive expertise about local flooding issues. These stakeholder sessions utilized the Vulnerability, Consequences and Adaptation Planning Scenarios (VCAPS) structural modeling approach, with the specific intention of examining how flood risk translates into social, economic, health and other consequences in St. Marys. The group also identified potential strategies for preventing or responding to these impacts.

What the project team found based upon local feedback was concern about the stormwater and wastewater treatment systems and property vulnerability, especially historic structures. Participants also identified specific locations of concern, such as the historic downtown area and Point Peter. Many residents expressed that noreasters are more of a concern than hurricanes, as well as beliefs that the city is fairly protected from hurricanes by the Georgia Bight. Co-producing knowledge with the local community provided the project team with an opportunity to facilitate a more comprehensive planning process, as well as identify where additional educational efforts would be best served.



INTERVIEWS

In February and March 2014, the project team conducted 20 one-hour interviews with key stakeholders with knowledge about local flooding issues. These interviews endeavored to gain insight into the local concerns and priorities in relation to flooding. The confidential conversations explored local opinions on how weather and climate hazards might affect planning processes and how local governments are able to respond. This included identifying places most vulnerable to flooding and past efforts to respond to these threats. The interviews also touched on livelihood impacts, barriers to taking action and interview-ees' feelings about their own abilities to contribute to the community's decision-making process.

The project team then conducted qualitative data analysis of the transcribed interviews using NVivo software to capture insights and patterns within the text (Figure 3.1). This analysis revealed that interviewees identified the following areas as vulnerable to flooding and that are considered important by residents and members of the community:

- DOWNTOWN ST. MARYS Downtown St. Marys contains historic properties that are already vulnerable and
- POINT PETER Site of a housing development, as well as the archaeological ruins and marker of a U.S. Army post established in 1795. The battery experienced the last invasion and occupation by foreign troops of the U.S. mainland, which occurred as part of the War of 1812.
- HOUSING According to 2014 U.S. Census data, the City of St. Marys contains over 7,400 housing units with a median value of \$166,000. Approximately, 11 percent of these properties are within the flood hazard area, including many of the City's historical structures.

The analysis also revealed public perceptions that noreasters pose a significant risk to St. Marys, as well as that the Georgia Bight shields St. Marys from hurricanes. Research indicates that the latter sentiment is not accurate, which indicated a need for further analysis and educational outreach to help shift public perceptions of the risk for future hurricanes in the area and potential impacts and damages that could affect the region in the future.

The anonymous results of the interviews were used to develop a series of meetings with planning officials and additional key stakeholders to diagram the environmental impacts of flooding hazards and potential responses, collaboratively building scenarios of how changes in zoning and ordinance might affect St. Marys' resilience to weather and climate hazards.



FIGURE 3.1: TOP 15 WORDS MOST MENTIONED IN ST MARYS INTERVIEWS

SEA GRANT TOWN HALL MEETING

On March 19, 2014, St. Marys residents and municipal leaders attended a Sea Grant Town Hall Meeting to learn about resilience planning efforts and to share feedback on issues related to flooding, sea-level rise and storm surge.

The public meeting included summaries of the plan by researchers from Georgia Sea Grant, UGA Carl Vinson Institute of Government, UGA Marine Extension and North Carolina Sea Grant. Attendees had the opportunity to ask questions and offer comments. They also provided input into the plan's development by providing feedback through clicker voting keypads.

Results of key questions included in the audience polling at the Sea Grant Town Hall meeting:







of respondents think Camden County is most important for helping



How urgent do you think it is to begin addressing sea- level rise in St. Marys?	of respondents answered very urgent		72% of respondents think
	What is the biggest obstacle for taking action on flood issues?		historic downtown is most vulnerable to flooding
LACK OF AGREEMENT ABOUT PROBLEM	0%		
LACK OF AUTHORITY	0%		
LACK OF AGREEMENT ABOUT WHAT TO DO	0%		
LACK OF KNOWLEDGE		100%	
	0%		

What collaborations do you think are most important for helping St. Marys address flooding issues?



81% of respondents think winter storms are creating the worst flooding in St. Marys

FACILITATED DISCUSSIONS ON FLOOD VULNERABILITY

The Vulnerability Consequences and Adaptation Planning Scenarios (VCAPS) process was developed by the Social and Environmental Research Institute, the Carolinas Integrated Sciences and Assessments Center at the University of South Carolina, and the South Carolina Sea Grant Consortium.²⁰

To date, vCAPS has been used to explore hazard mitigation and climate adaptation in coastal communities in North Carolina, South Carolina and Georgia. vCAPS is a facilitated participatory process based in the causal structure of hazards and vulnerability assessment. The specific purpose of vCAPS is to assist communities in diagramming the outcomes and consequences of climate stressors on aspects of municipal management. Real-time projection of a diagram documenting the group conversation assists community members with discussion of potential adaptation and response options that public and private entities may implement, while also facilitating consideration of positive outcomes as well as potential negative consequences of interventions.

Participants decided to categorize flooding occurrences as either episodic (heavy rainstorms, upstream flooding, storm surges and category 1 hurricanes) or long-term events (rise in the water table and sea-level rise), evaluating their effects on three important issues:

- **1** Stormwater infrastructure;
- **2** Wastewater treatment infrastructure;
- **S** Managing risks to private properties.

Additionally, the group prioritized the issue of emergency management planning; however, because the City of St. Marys and Camden County are currently addressing this topic through ongoing Hazard Mitigation Plan updates, a decision was made to focus the discussion on flood planning in relation to stormwater, wastewater and private property concerns. These ideas, generated by St. Marys participants, are summarized in the following sections.



DR. JESSICA WHITEHEAD USES A DIAGRAMMING TOOL TO CAPTURE DISCUSSION ON FLOOD VULNERABILITY

Scenario 1: Stormwater and Wastewater Treatment Planning

Vulnerability discussions indicated that episodic and long-term flooding can potentially impact both stormwater and wastewater management (Figure 3.2). Although stormwater and wastewater are distinct management concerns, it was decided that both issues must be considered simultaneously in St. Marys. Failures in the drainage and retention of stormwater during flood events could lead to excess water in wastewater systems, thus overloading treatment plants and potentially causing wastewater spills.

Participants identified two major outcomes of episodic flooding in St. Marys. The first outcome relates to **water quality**. Water flowing over impervious surfaces and developed areas can cause runoff. This runoff has increased volumes and velocities in comparison to water flowing over a natural or vegetated landscape. Runoff often picks up and transports sediment and other nonpoint source pollution as it moves over impervious surfaces, reducing water quality.

Water can also collect in stormwater retention ponds. When capacity is reached, overflow may occur. This overflow could result in flooding, which can cause property damage. The resulting flow into marshes carries sediments and contaminants that reduce water quality. Water may also sit in ponds for days, and this sitting water could create health problems. Participants additionally expressed concerns about possible wastewater overflows from treatment plants during flood events that could impact water quality and become a health hazard.

The second major outcome from episodic flooding discussed was **power outages**, which could affect both wastewater treatment plants and lift stations. The occurrence of flooding at non-functional plants and stations could lead to sewage spills and water contamination, resulting in health hazards and heavy fines for the City.

The group noted several public and private sector actions that could reduce the negative consequences of flooding on stormwater and wastewater management in St. Marys. The City's drainage capacity could be increased by cleaning ditches more frequently, planting more vegetation and using permeable pavement. Other suggestions included educating the public on the effects of littering and stormwater retention laws, as well as improving litter law enforcement. Comments were made concerning the need to educate homeowners who commonly uncover sewer drains as a way of reducing flooding on their properties.

To reduce the negative effects of power outages, participants discussed flood-proofing lift stations and strategically placing generators for back up. They also discussed raising lift stations to reduce flood risks and partnering with the Naval Base to interconnect wastewater systems. Failures in the drainage and retention of stormwater during flood events could lead to excess water in wastewater systems.





FIGURE 3.2. VCAPS DIAGRAM OF STAKEHOLDER CONCERNS ABOUT STORMWATER AND WASTEWATER PLANNING

VCAPS Diagram of Stakeholder Concerns About Stormwater and Wastewater Planning



Scenario 2: Managing Risks To Properties

In the second session, the group discussed the impacts of episodic flooding and long-term flood conditions on properties (Figure 3.3). Participants identified that surface water runoff is currently the most common cause of flooding, and, consequentially, water damage to buildings. Additionally, the group mentioned that wind damage could leave buildings vulnerable to rainfall during storm events, which could lead to properties experiencing water damage.

Private property damage generates expenses to home and business owners. Extensive damage could cause property loss and lead to derelict structures. Participants expressed significant concern over the historic character of the City and the protection of historic properties. Damage to such structures could result in the abandonment of property due to the extensive financial burden of restoration, as well as the potential for property loss. As a historic City, the loss of historic properties could lead to loss of character, and, consequentially, loss of tourism. In return, abandonment and loss of property could reduce the quality of life and the morale of the community and also render the City unattractive to potential future investors.

When focusing on the long-term flood risks and the impacts to properties, participants discussed how erosion affects properties along waterways. Erosion currently occurs as a result of water movement caused mainly by waves during storms and by boats. However, as sea levels rise, there is concern that erosion will increase, leading to a reduction in property size and jeopardizing built structures. Additionally, rising water and inundation could impact the City's waterfront park, and saltwater intrusion could kill yards.

The group noted strategies that could be used to reduce the risks of property damage, such as stipulating height regulations and educating property owners on how to protect buildings and properties. Discussions also pointed to the possibility of raising buildings

"Ninety percent of the historic structures in our historic district have their lowest floor elevation located below the current 100-year flood elevation."

> WILLIAM DELOUGHY, FORMER ST. MARYS MAYOR

and educating the population on the benefits of such measures in the reduction of flood insurance premiums. However, there were concerns that property owners might become overwhelmed and that additional regulations and costs could potentially inhibit people from moving to St. Marys and/or investing in the City.

From a historic standpoint, the group discussed constraints currently in place for adapting historic buildings and suggested the revision of codes pertaining to such structures, which would allow property owners to flood-proof their historic properties. Alternatively, the group discussed taking pictures of existing historic landmarks, as a way of registering their existence and preserving the memory of properties that

could be lost in future flood events. When discussing the waterfront park, participants suggested looking at solutions used by the National Parks Service for similar properties as a way of deciding upon future actions.









FIGURE 3.3. VCAPS DIAGRAM OF STAKEHOLDER CONCERNS ABOUT PRIVATE PROPERTY FLOODING

VCAPS Diagram of Stakeholder Concerns About Private Property Flooding



20 Webler, T., S. Tuler, K. Dow, J. Whitehad, and N. Kettle. 2016. Design and evaluation of a local analytic-deliberative process for climate adaptation planning. The International Journal of Justice and Sustainability 21:166–188.

CHAPTER 4:

Flood Vulnerability Assessment

Following the vCAPS scenario-building exercises, a technical flooding vulnerability assessment, including consideration of future hydro-logic conditions associated with sea-level rise, was conducted for the City of St. Marys. This vulnerability assessment was developed through integration of various datasets collected and analyzed through geographic information system (GIS) methods, most of which were implemented with ESRI'S Arc GIS 10.2.2 software platform.

Public assets that were assessed for current and future flood vulnerability in the City of St. Marys include roads, police stations, fire stations, schools, wastewater treatment facilities, and stormwater infrastructure. Specific vulnerability assessment results for these public facilities are provided in this report. Private buildings and associated property were also assessed for current and future flood vulnerability. Vulnerability assessment results for private property are pooled to a City-wide scale. Base flood heights for 10-year, 50-year, 100-year, and 500-year storm events under current conditions were based upon Flood Insurance Rate Maps (FIRMS) as defined through the Federal Emergency Management Agency's 2005 Flood Insurance Study for Camden County.²¹

Various sea-level rise scenarios were added onto these currently defined flood heights to assess future flood vulnerability.

DATASET INVENTORY

A variety of GIS datasets, as collected from governmental agency sources, were used to develop the flood vulnerability assessment for the City of St. Marys (Table 4.1). For consistency of analysis, all original datasets were transformed into the Georgia East (FIPS 1001) State Plane projected coordinate system, as referenced to the North American Datum of 1983 (NAD83) and incorporating the National Adjustment of 2011 (NA2011).

ORIGINAL DATASET DESCRIPTION	FILE NAME	SOURCE
Digital Elevation Model (Raster)	CamdenDEM.tif	Coastal Regional Commission of Georgia, as derived from LiDAR points obtained with the 2010 Coastal Georgia Elevation Project
Digital Flood Insurance Rate Map (DFIRM) (Polygon)	s_fld_haz_ar.shp (For Flood Insurance Study 13039, Camden County, GA)	Federal Emergency Management Agency
Property Parcels with 2013 valuations (Geodatabase)	Camden_2013.gdb	Camden County Tax Assessor's Office
Roads (Geodatabase)	Roads.mdb	City of St. Marys
Schools (Point)	Schools.shp	City of St. Marys
Fire and Police Stations (Points)	Fire_Police_stations.shp	City of St. Marys
Building Footprints (Polygon)	Buildings.shp	Coastal Regional Commission of Georgia
Stormwater infrastructure (Geodatabase)	StormWaterCollection System.mdb	City of St. Marys
Wastewater treatment plants (Point)	WWTP.shp	City of St. Marys
City limits for St. Marys (Polygon)	St_Marys.shp	City of St. Marys

TABLE 4.1: ORIGINALGEOGRAPHIC INFORMATIONSYSTEM (GIS) DATASET LIST

ELEVATION

A digital elevation model (DEM) of the City of St. Marys and nearby areas of surrounding Camden County is shown in Figure 4.1. This DEM is derived from Light Detection and Ranging (LiDAR) points collected through the 2010 Coastal Georgia Elevation Project and is vertically referenced to the North American Vertical Datum of 1988 (NAVD88). Tide ranges and tidal elevation datums for coastal waters in and around the City of St. Marys closely match those recorded at NOAA tide gauge #8720030, located in nearby Fernandina Beach, FL (Figure 4.2). Current elevation datums for the Fernandina Beach tide gauge are based upon the 1992 National Tidal Datum Epoch, which includes water levels from 1983–2001.

The lowest areas of St. Marys are composed of undeveloped tidal saltwater creeks and marshes, which have elevations that are below or just above the North American Vertical Datum of 1988 (NAVD88). The developed portions of St. Marys are located on elevations that range between approximately 5 feet and 35 feet above NAVD88, with the lowest-lying developed areas generally found near coastal marshes and waterways. The highest areas of St. Marys, at over 60 feet above NAVD88, are located on a fill mound just east of waste ponds associated with the former Durango-Georgia paper mill.



Private buildings and associated property were also assessed for current and future flood vulnerability.

> FIGURE 4.1: ELEVATION MAP OF ST. MARYS, GA, AND VICINITY



Datums for 8720030 Fernandina Beach, FL

ALL FIGURES IN FEET RELATIVE TO STATION DATUM

FIGURE 4.2: TIDAL DATUMS FOR FERNANDINA BEACH, FL. DATUMS REFERRED TO IN THIS REPORT INCLUDE MEAN HIGHER HIGH WATER (MHHW), NORTH AMERICAN VERTICAL DATUM OF 1988 (NAVD88), MEAN SEA LEVEL (MSL), AND MEAN LOWER LOW WATER (MLLW). THE DIF-FERENCE BETWEEN MHHW AND MLLW, OR THE AVERAGE HIGHEST HIGH TIDE AND AVERAGE LOWEST LOW TIDE EACH DAY, IS REFERRED TO AS THE GREAT DIURNAL RANGE (GT). IMAGE ADAPTED FROM https://tidesand currents.noaa.gov/datums.html?id=8720030



SEA-LEVEL RISE AND FLOOD VULNERABILITY THRESHOLDS

Current technical guidance from NOAA defines four scenarios of sea-level rise for use in local planning (see Table 4.2).²² It is important to note that all future sea-level rise scenarios, as developed by NOAA or other federal agencies such as the United States Army Corps of Engineers, are each based upon a different set of technical assumptions. At this time, it is impossible to know for sure which scenario will most closely match actual conditions that transpire over the coming decades. Instead, it is generally recommended to use a risk-based approach for scenario-building. Under such as risk-based approach, higher tolerance for risk is equated to use of a lower sea-level rise scenario, while lower tolerance for risk entails use of a higher sea-level rise scenario.²³

The *Low* scenario assumes that future global warming and climate change will be minimal through 2100. For the City of St. Marys, this scenario would entail a straight continuation of the linear trend of sea-level rise already observed at Fernandina Beach since the installation of the tide gauge in 1897. Use of the *Low* scenario is only recommended for low-value infrastructure that can be readily moved, may be easily replaced, and would not be cause for much societal concern if flooded. It could be appropriate to use the *Low* sealevel rise scenario when siting a low-cost storage building that contains easily replaceable materials and has an expected life-cycle of less than 25-years.

The *Intermediate Low* scenario assumes some amplification of sea-level rise in the twenty-first century due to thermal expansion of oceans and continued ice melt in Greenland, Antarctica, and mountain glaciers. Empirical support for this amplified sea-level rise is suggested by the higher rate (0.126 in/yr) of sea-level rise recorded since 1992 by satellite altimetry as compared to the rate (0.067 in/yr) calculated by integration of the global tide gauge data record before 1992.²⁴ The *Intermediate Low* scenario is the minimum rate of sea-level rise recommended for most regular planning purposes.

The *Intermediate High* scenario assumes an increasing rate of sea-level rise beyond that observed by historical satellite altimetry, primarily due to an increased rate of ice sheet melt in Greenland and Antarctica due to global warming and climate change associated with growing atmospheric concentrations of greenhouse gases. The *Intermediate High* scenario is generally recommended for higher-value infrastructure, such as a wastewater treatment facility, that would be expensive to relocate and would cause serious social concern if flooded before 2100.



The *High* scenario assumes the onset of catastrophic ice sheet melt in Greenland and Antarctica that prompts global sea-level rise rates similar to those that occurred approximately 13,000 years ago at the end of the last Ice Age. The *High* scenario is recommended when planning for infrastructure that has very little risk tolerance and would cause extreme societal disruption if flooded. Nuclear power plants and hazardous chemical facilities are examples of such low-risk tolerance infrastructure.²⁵

The High scenario assumes the onset of catastrophic ice sheet melt in Greenland and Antarctica. Many sea-level rise vulnerability assessments utilize projected changes in the mean higher high water (MHHW) level as the threshold for determining future vulnerability to flood inundation.²⁶ A straightforward interpretation of this threshold is that, unless protective measures are taken, areas below MHHW will be vulnerable to tidal flooding on an almost daily basis. It is generally assumed that daily inundation from saltwater would make maintenance of most human development, such as roads and buildings, difficult or even impossible. As shown in Figure 4.2, the 1992 MHHW datum is 2.74 feet higher than NAVD88 and 3.29 feet higher than 1992 Mean Sea Level (MSL) at the Fernandina Beach tide gauge. A summary of projected changes in MHHW, as referenced to NAVD88, at Fernandina Beach under the different NOAA sea-level rise scenarios is provided in Table 4.3.

It is, however, increasingly recognized that stresses to human development due to sealevel rise occur well before an area is flooded on an almost daily basis. For example, spring tides that produce high tides substantially higher than MHHW occur naturally each month during the full moon and new moon cycles. The highest spring tides of the year, which generally occur during full and new moon cycles in the fall months at Fernandina Beach, are colloquially called "king tides." Such king tides are highly predictable and are naturally associated with oceanographic and astronomical cycles, especially the positions of the moon and sun relative to earth. Weather factors, such as strong on-shore winds and storm conditions, also regularly result in high tides that substantially exceed MHHW.



YEAR	LOW	INTERMEDIATE LOW	INTERMEDIATE HIGH	HIGH
1992	0	0	0	0
2015	0.15'	0.20'	0.30'	0.42'
2045	0.35'	0.60'	1.15'	1.79'
2065	0.51'	0.96'	2.01'	3.21'
2100	0.72'	1.75'	4.05'	6.67'

TABLE 4.2: LOCALLY ADJUSTED SEA-LEVEL RISE VALUES FOR THEFERNANDINA BEACH, FL, TIDE GAUGE, BY NOAA SEA-LEVEL RISESCENARIO AND AS REFERENCED TO 1992 MEAN SEA LEVEL.

YEAR	LOW	INTERMEDIATE LOW	INTERMEDIATE HIGH	HIGH
1992	2.74'	2.74'	2.74'	2.74'
2015	2.89'	2.94'	3.04'	3.16'
2045	3.09'	3.34'	3.89'	4.53'
2065	3.25'	3.70'	4.75'	5.95'
2100	3.46'	4.49'	6.79'	9.41'

TABLE 4.3: MEAN HIGHER HIGH WATER (MHHW) ESTIMATES FOR THEFERNANDINA BEACH, FL, TIDE GAUGE, BY NOAA SEA-LEVEL RISE SCENARIOAND AS REFERENCED TO NAVD8828

The term "nuisance flooding" is often used to describe the moderate flooding conditions that can occur in localized areas during king tide or storm tide cycles. At Fernandina Beach, the nuisance flooding threshold is defined as 1.94 feet above MHHW, which translates into 4.68 feet above NAVD88.²⁷ As noted in Chapter 2, the nuisance flooding threshold was exceeded during seven tide cycles at Fernandina Beach in 2015. For the purpose of this report, the current nuisance tide level is used as the elevation threshold for assessing current and future vulnerability to king tides. Table 4.4 provides a summary of projected changes in the king tide level, as referenced to NAVD88, at Fernandina Beach under the different sea-level rise scenarios.

The storm surge associated with the passage of Hurricane Matthew in October 2016 produced the highest water levels (4.17 feet above 1992 MHHW, or 6.91' above NAVD88) observed at the Fernandina Beach tide gauge since the direct landfall of a major hurricane at Cumberland Island in 1898. High water mark data collected by the United States Geological Survey following Hurricane Matthew, as shown in and near the City of St. Marys in Figure 4.3, indicate that water levels in the downtown waterfront area of St. Marys were similar to those observed at the Fernandina Beach tide gauge. This storm, which produced substantial damage in low-lying areas of St. Marys, provides a reference for future vulnerability to similar storms that may be amplified by sea-level rise. Table 4.5 summarizes the additive changes in a high water level event similar to Hurricane Matthew under the NOAA sea-level rise scenarios.

YEAR	LOW	INTERMEDIATE LOW	INTERMEDIATE HIGH	нідн
2015	4.68'	4.68'	4.68'	4.68'
2045	4.88'	5.08'	5.53'	6.07'
2065	5.01'	5.44'	6.39'	7.49'
2100	5.25'	6.23'	8.43'	10.95'

 TABLE 4.4: KING TIDE HEIGHTS FOR ST. MARYS, GA, BY NOAA SEA-LEVEL

 RISE SCENARIO AND AS REFERENCED TO NAVD8829

YEAR	LOW	INTERMEDIATE LOW	INTERMEDIATE HIGH	нідн
2015	6.91'	6.91'	6.91'	6.91'
2045	7.11'	7.31'	7.76'	8.30'
2065	7.24'	7.67'	8.62'	9.72'
2100	7.48'	8.46'	10.66'	13.18'

TABLE 4.5: PREDICTIONS OF WATER LEVELS AT FERNANDINA BEACH DURINGAN EVENT SIMILAR TO THAT OBSERVED DURING HURRICANE MATTHEW (2016),BY NOAA SEA-LEVEL RISE SCENARIO AND AS REFERENCED TO NAVD8830




ROADS VULNERABILITY

A series of analyses were performed in ArcGIS 10.2.2 to determine tidal flooding vulnerability for roads in the City of St. Marys in the years 2015 (current condition), 2045 (30-year horizon), 2065 (50-year horizon), and 2100 (end-of-century). The base case for all years in this analysis was king tide flooding under the *Intermediate High* sea-level rise scenario. An assessment of road miles vulnerable to possible inundation (i.e., below future MHHW) at the year 2100 under the *High* sea-level rise scenario was also performed.³²

The first step of the analysis was to clip the digital elevation model (Camdendem.tif) to the geographic extent of the City of St. Marys (St_Marys.shp). Cells in the clipped digital elevation model (StMrysdem.tif) with elevation values below the respective elevation threshold for each flood scenario (Table 4.3 for 2100 MHHw; Table 4.4 for king tide values) were selected and transformed into a series of simplified polygon shapefiles. These shapefiles were then used to clip the roads polyline feature class (from Roads.mdb) for each flood scenario. Using this procedure, all polyline road extents within the output datasets were thus identified, through geographic coincidence with values in the digital elevation model that are below the defined flood threshold, as vulnerable to tidal flooding for the given sea-level rise scenario.

Table 4.6 provides a summary of the road miles vulnerable to tidal flooding under each scenario. Figure 4.4 provides a map visualization of the roads vulnerability assessment. The road that shows the most current and future vulnerability to king tide flooding is St. Marys St. along the historic downtown waterfront. A close-up of the roads vulnerability analysis for downtown St. Marys is shown in Figure 4.5.

FIGURE 4.3: HIGH WATER MARKS, IN FEET REFERENCED TO NAVD88, RECORDED BY THE UNITED STATES GEOLOGICAL SURVEY DURING HURRICANE MATTHEW, OCTOBER 7, 2016.³¹ BY WAY OF COMPARISON, AN AVERAGE DAILY HIGH TIDE IN ST. MARYS IS APPROXIMATELY 2.74 FEET ABOVE NAVD88.

TOTAL	2015	2045	2065	2100
ROAD MILES	KING TIDE	KING TIDE	KING TIDE	KING TIDE
162.2	1.0 (0.6%)	2.7 (1.7%)	7.2 (4.4%)	24.0 (14.8%)

TABLE 4.6: ROAD MILES (AND PERCENTAGE OF ORIGINAL ROAD MILES)IDENTIFIED AS VULNERABLE TO TIDAL FLOODING IN THE CITY OF ST.MARYS WITH KING TIDE CONDITIONS ASSESSMENTS UNDER THE NOAAINTERMEDIATE HIGH SEA-LEVEL RISE SCENARIO FOR EACH GIVEN YEAR.



FIGURE 4.4: VULNERABILITY OF CURRENT ROAD SEGMENTS IN CITY OF ST. MARYS, GA, TO CURRENT AND FUTURE KING TIDES WITH INTERMEDIATE HIGH SEA-LEVEL RISE





PUBLIC FACILITIES

A flood vulnerability analysis was performed for police stations, fire stations, schools, and wastewater treatment facilities located within the City of St. Marys, as well as for buildings on parcels owned by the City of St. Marys. Most of this analysis was performed through a Zonal Statistics operation in ArcGIS 10.2.2 that extracted minimum ground elevation values, as obtained from the LIDAR-based DEM, within building footprint polygons associated with the given structures. For facilities in which building footprint polygons were not available at the time of the analysis, elevation values were extracted from point locations provided by the City of St. Marys (and verified through aerial photography).³³ The designated FEMA 100-year flood height, also known as the base flood elevation, at the site of each building was determined using a spatial join procedure.

The results of this analysis, as summarized in Table 4.7, indicate that the St. Marys Submarine Museum—located along the historic downtown waterfront—is the only listed public facility that shows a ground elevation lower than the currently designated 100-year base flood elevation. The Submarine Museum site also shows potential vulnerability to king tide flooding by 2045 under an *Intermediate High* sea-level rise scenario. All other listed public facilities are either located outside of the 100-year floodplain or show ground elevations somewhat higher than the designated base flood elevation for the particular site. Three publicly owned facilities—City Hall, the Liberty Tree Water Plant Site, and the St. Marys Women's Club—show potential vulnerability to a Matthew-sized flood event at 2100 under the *Intermediate High* sea-level rise scenario.

FACILITY NAME	BUILDING ELEVATION	BASE FLOOD ELEVATION	FLOOD RISK, SLR SCENARIO
St Marys Submarine Museum	5.2	11.0	King Tide, 2045 Intermediate High
City Hall	9.5	N/A	Matthew, 2100 Intermediate High
Liberty Tree Water Plant Site	9.5	N/A	Matthew, 2100 Intermediate High
St Marys Women's Club	9.6	N/A	Matthew, 2100 Intermediate High
St Marys Elementary School	10.7	9.0	Matthew, 2100 High
Orange Hall	11.0	N/A	Matthew, 2100 High
St Marys Colerain Fire Station	11.6	N/A	Matthew, 2100 High
Point Peter Wastewater Treatment Plant	11.6	10.0	Matthew, 2100 High
City Library	12.3	N/A	Matthew, 2100 High
Scrubby Bluff Wastewater Treatment Plant	14.0	N/A	N/A
Mary Lee Clark Elementary School	15.1	N/A	N/A
Sugarmill Elementary School	17.2	N/A	N/A
Industrial Park S-2	18.2	N/A	N/A
St Marys Dandy Fire Station	18.4	N/A	N/A
Airport	19.9	N/A	N/A

FIGURE 4.7: TABLE 4.7: ESTIMATED GROUND ELEVATION OF BUILDINGS, 100-YEAR FEMA BASE FLOOD ELEVA-TION (IN FEET ABOVE NAVD88), AND SEA-LEVEL RISE (SLR) FLOOD RISK FOR GIVEN PUBLICLY-OWNED BUILDINGS WITHIN THE CITY OF ST. MARYS. A VALUE OF N/A FOR THE BASE FLOOD ELEVATION MEANS THAT THE FACILITY WAS NOT LOCATED IN THE 100-YEAR FLOODPLAIN AT THE TIME OF THIS STUDY. A VALUE OF N/A FOR THE FLOOD RISK, SLR SCENARIO COLUMN MEANS THAT THE FACILITY WOULD NOT BE VULNERABLE TO A MATTHEW-SIZED STORM SURGE AT THE HIGHEST SEA-LEVEL RISE SCENARIO BY 2100.



FLOOD VULNERABILITY ASSESSMENT FOR ALL STRUCTURES

A comprehensive 50-year flood damage assessment, including increased future vulnerability due to sea-level rise scenarios, was conducted for all buildings in St. Marys that fall within the designated FEMA floodplain. This includes the standard 100-year floodplain that comprises the special flood hazard area, as well as those areas outside of the special flood hazard area that are designated as within the 500-year floodplain. The 100-year floodplain is also known as the "one-percent floodplain," as it is estimated that there is at least a one-percent chance (i.e., one flood per 100 years) of a flood impacting all areas within this floodplain in any given year.

The property vulnerability analysis was performed using a customized adaptation of sea-level rise vulnerability assessment and monetization methods developed for NOAA by the Eastern Research Group, Inc.³⁴ ArcGIS 10.2.2 was used to derive ground elevation statistics for all building footprint polygons (n = 6,436) within the City of St. Marys, as defined by the available building footprint layer obtained from the Coastal Regional Commission of Georgia. The underlying ground elevation data were obtained from the Coastal Georgia LIDAR digital elevation model. Floodplain categorizations and associated base flood elevation definitions from the current digital flood insurance rate map (DFIRM) were then attached to each building footprint using a spatial join procedure. Building values were estimated using a spatial join procedure in which appraised parcel values from Camden County were appended to associated buildings.³⁵

Of the 6,436 original building footprints within the City of St. Marys, a total of 1,204 were located wholly or partially within the designated 100-year floodplain boundary. This included 1,199 within AE zones, which are designated as having at least a one-percent annual risk of a still water flood event. The other five buildings were located within VE zones, which are designated as having at least a one-percent annual risk of wave action damage in addition to still water flooding. Most buildings that have a federally backed mortgage and are located within either an AE or VE zone are required to have flood insurance. An additional 1,897 buildings were located within the 500-year floodplain, which is used to designate areas with at least 0.2 percent annual flooding risk. Buildings located within the 500-year floodplain, but outside of the 100-year floodplain, have no mandatory flood insurance requirement, although purchase of flood insurance is still recommended due to the possibility of catastrophic flood events.

For all areas within the 100-year floodplain, future flood height risk was calculated at decadal intervals (i.e., 2015, 2025, 2035, 2045, 2055, and 2065) by adding the NOAA *Low*, *Intermediate-Low*, and *Intermediate-High* sea-level rise scenario values to the 100-year base flood elevation from a 2015 baseline. A similar calculation was performed to add sea-level rise onto the 10-year (10-percent), 50-year (two-percent), and 500-year (0.2 percent) flood heights. For areas only within the 500-year floodplain, sea-level rise was added onto the defined 500-year flood height. The original flood heights for the 100-year flood event were defined for each special flood hazard area polygon within the DFIRM shapefile. All 10-year, 50-year, and 500-year flood event heights were derived from the Camden County Flood Insurance Study.³⁶



FLOOD DEPTH (FEET)	DAMAGE (% OF ASSESSED VALUE)
0	0%
1	2.5%
2	13.4%
3	23.3%
4	32.1%
5	40.1%
6	47.1%
7	53.2%
8	58.6%
9	63.2%
10	67.2%

FIGURE 4.8: DEPTH DAMAGE RELATIONSHIP APPLIED FOR FLOOD EVENTS IN THE CITY OF ST. MARYS

YEAR	10-YEAR	50-YEAR	100-YEAR	500-YEAR
	(10%)	(2%)	(1%)	(0.2%)
2015	\$146,570	\$14,460,900	\$27,977,200	\$110,895,500

FIGURE 4.9: ESTIMATED PROPERTY DAMAGES IN THE CITY OF ST. MARYS, BY GIVEN FLOOD EVENT AT YEAR 2015 BASELINE

SCENARIO	10-YEAR (10%)	50-YEAR (2%)	100-YEAR (1%)	500-YEAR (0.2%)
Low	\$248,435	\$16,809,742	\$18,529,422	\$119,322,878
Int-Low	\$615,711	\$20,876,869	\$36,213,482	\$133,501,939
Int-High	\$2,193,537	\$32,505,526	\$49,081,770	\$165,957,380

FIGURE 4.10: ESTIMATED PROPERTY FLOOD DAMAGES TO CURRENT STRUCTURES IN THE CITY OF ST. MARYS IN 2045, BY SEA-LEVEL RISE SCENARIO AND BY 2015 ASSESSED VALUE

SCENARIO	10-YEAR (10%)	50-YEAR (2%)	100-YEAR (1%)	500-YEAR (0.2%)
Low	\$317,614	\$16,021,642	\$28,468,782	\$125,076,703
Int-Low	\$1,397,458	\$24,634,483	\$39,100,935	\$156,493,545
Int-High	\$8,905,013	\$60,799,055	\$77,402,095	\$231,404,195

FIGURE 4.11: ESTIMATED PROPERTY FLOOD DAMAGES TO CURRENT STRUCTURES IN THE CITY OF ST. MARYS IN 2065, BY SEA-LEVEL RISE SCENARIO AND BY 2015 ASSESSED VALUE

Flood heights affecting each particular building were obtained by subtraction of the high water elevation for a given flood event from the minimum ground elevation associated with a given building footprint. Dollar-based damages to individual buildings were then assessed through application of a generic depth-damage relationship, as adapted from the United States Army Corps of Engineers (Table 4.8),³⁷ to the annualized probability of the given flood height event.

Table 4.9 provides a summary for the baseline of expected dollar damages, as summed across the City of St. Marys, if the area was impacted by a 10-year, 50-year, 100-year, or 500-year flood event. The 2015 damage values are based upon an assumption of the current base flood elevation (i.e., no attributed sea-level rise). The initial assessed value for buildings in the City of St. Marys was \$1.8 billion.

Dollar damage values for the given flood events at subsequent decadal increments were then calculated for each sea-level rise scenario through the 2065 planning horizon. The results for 2045 (30-year planning horizon) are presented in Table 4.10. The 2065 results (50-year planning horizon) are in Table 4.11.

It is important to be clear that the single event calculations (Tables 4.9–4.11) provide damage estimates for an actual occurrence of the given flood event. However, the risk of flood events is generally assessed through an annual probability of occurrence. Because a 100-year flood event has the equivalent of a one-percent chance of occurring in a given year, the annualized damages for the 100-year event are assessed at one percent of what is calculated by the single-event approach. Similarly, a 10-year event is annually assessed at 10 percent of the single event damage estimate, the 50-year event is assessed at 0.2 percent.

It is also generally accepted that damages from future flood events should be "discounted" according to a "net present value" (NPV) time function. This is based upon the assumption that individuals and societies are willing to pay more to avoid damages that will occur in the near future, with less willingness to pay to avoid future damages.³⁸ A discount rate of 3.3 percent was chosen for this project in collaboration with City of St. Marys public officials and stakeholders.

LOW	INTERMEDIATE -LOW	INTERMEDIATE -HIGH
\$24,235,800	\$28,427,100	\$41,218,300

 TABLE 4.12: 50-YEAR NET PRESENT VALUE (NPV) FLOOD

 VULNERABILITY ASSESSMENT FOR THE CITY OF ST. MARYS,

 BY NOAA SEA-LEVEL RISE SCENARIO.⁴¹ THE TOTAL ASSESSED

 VALUE OF PROPERTIES IN THE CITY WAS \$1.8 BILLION.

Integration of the probabilistic storm damages, along with application of the 3.3 percent annualized discount rate,³⁹ was used to produce a NPV-equivalent flood vulnerability assessment for the City of St. Marys.⁴⁰ This assessment cumulatively covers flood risk, as adjusted to increased water heights for flood events due to sealevel rise and discounted property values, for the 50-year period from 2015 to 2065. The results of this NPV assessment are summarized in Table 4.12.

ADAPTATION OPTIONS FOR AVOIDANCE OF FLOOD DAMAGES

Option 1: Hard Barrier (not recommended)

A common infrastructure option for avoiding private property flood losses associated with coastal flooding risk is construction of a hardened physical barrier, such as an enhanced sea wall, levee, and/or dyke. The clear advantage of such a barrier is that, in certain circumstances, damages from flood waters within the built environment can be entirely avoided. For this reason, some large municipalities, such as New York City, are currently pursuing hardened barriers as a primary flood resilience strategy.⁴²

Construction of a traditional physical barrier option in the City of St. Marys, however, is inherently problematized by the lengthy linear extent (~21 miles) of the exposed waterfront and marshfront shorelines that are adjacent to structures within the City's delineated floodplain. The construction cost of an engineered sea wall of sufficient height and strength to prevent a surge-associated flood loss along the full 21 miles of developed coastal extent is conservatively estimated at \$127.5 million.⁴³ Such a construction cost is several times higher than the potential 50-year avoided NPV loss of \$41.2 million under the *Intermediate-High* sea-level rise scenario (Table 4.12).

This relatively small potential benefit relative to the construction cost expenditure makes the hard barrier option unattractive to pursue from even a very limited benefit-cost perspective. Other societal costs from a large sea wall — such as reduced waterfront aesthetics, increased erosion and habitat destruction in coastal marshlands, and long-term capital maintenance expenditures⁴⁴ — further argue against municipal-scale pursuit of a large-scale, publicly funded hard barrier within the City of St. Marys at this time.



Option 2: Individual Property Adaptation (Recommended and Adopted)

On January 6, 2014, the St. Marys City Council unanimously passed an amendment to Section 54 of the City's Code of Ordinances for the purpose of flood hazard reduction. Among numerous other provisions, Section 54.6 of the ordinance specifically requires that newly constructed and substantially improved residential structures must be "elevated no lower than two feet above the base flood elevation," while newly constructed or substantially improved residential to be watertight to one foot above the base flood elevation."

These requirements exceed the National Flood Insurance Program's minimum standard, which is for new and substantially improved structures to simply be above the 100-year base flood elevation. The requirement would notably put all newly constructed or substantially improved residential structures in the City of St. Marys above the 100-year flood height with up to two-feet of sea-level rise, which is very near the NOAA *Intermediate-High* sea-level rise scenario for 2065 (2.01'). These flood hazard construction standards will result in drastically reduced potential flood damages within the City over time, including under a scenario that assumes substantially accelerated sea-level rise over the next 50-years.

Costs of elevating new structures — as well as elevating existing structures — are highly dependent on the size, design, and foundation type of the structure. However, a simple comparison of avoided damages per structure in the regulatory floodplain indicates that an average flood-proofing investment of between \$20,129 (*Low* sea-level rise) and \$34,234 (*Intermediate-High* sea-level rise) per structure would be likely to provide a positive benefit-cost return in terms of avoided property loss over the 50-year planning horizon.⁴⁵ Additional benefits such as lowered flood insurance rates and substantially reduced time of resident displacement, while not formally accounted in this analysis, can be expected to increase the benefits associated with individual property adaptation measures that follow guidelines established by the City's flood hazard ordinance.⁴⁶

STORMWATER VULNERABILITY ASSESSMENT

Discussions with stakeholders and public officials within the City of St. Marys indicated some concerns about the current functioning of the City's stormwater drainage system, particularly within the downtown historic district. A number of stakeholders gave specific reports of somewhat frequent flooding in low-lying streets and yards in the downtown area, and further noted that these flood events generally occur when heavy rainfalls happen to coincide with high tide cycles. Observations and knowledge that significant portions of the stormwater system in the historic downtown and other areas of the City discharge directly into tidal waterways, combined with apparent linkages between tide stage and rainfall flooding, raised additional concern that current stormwater issues could be substantially worsened by future sea-level rise.

During the data gathering phase of this project, the City of St. Marys supplied a comprehensive set of geographic information system (GIS) files that together provide a high level of detail about the City's stormwater infrastructure. Geographic information provided by these files include point locations for stormwater infalls and outfalls, linear extents for underground pipes, linear extents for drainage ditches, and polygon extent of retention and detention facilities. Importantly, the attribute information for infall and outfall points also includes specific elevation readings for belowground infrastructure (often referred to as invert elevation). Additional attribute information such as pipe shape, diameter, and construction material was also available for most underground stormwater pipes.

A range of current and future tide range scenarios, as based upon the Fernandina Beach tide gauge, were compared against the known invert elevations for stormwater infalls and outfalls in the City of St. Marys. This City-wide analysis was used to identify the current and future extent of underground stormwater infrastructure that is likely being pene-trated by tidewater, thus reducing drainage capacity during rainfall. The City of St. Marys stormwater database contains a total of 1,923 structures with defined bottom elevations, as referenced to NAVD88. The structures include 1,280 stormwater inlet and access points such as box culverts, catch basins, curb inlets, grated drop inlets, junction boxes, manhole accesses, and swale inlets. The other 643 structures are pipe outfalls that lead into ditches, retention ponds, swales, and receiving waters.

The baseline tidal penetration assessment is for structures with bottom elevations below the 1992 MHHW level, or 2.76' above NAVD88. A total of 148 stormwater structures, including 83 inlets and 65 outfalls, within St. Marys were identified as below this MHHW elevation. A large percentage of structures below 1992 MHHW are located in the City's historic



FIGURE 4.6: STORMWATER STRUC-TURES WITH UNDERGROUND ELEVATION LESS THAN CURRENT MEAN HIGHER HIGH WATER (MHHW) DATUM (2.76' ABOVE NAVD88), CITY OF ST. MARYS, GA. downtown waterfront area and are associated with outfalls that connect directly to the tidally influenced St. Marys River (Figure 4.6). Areas served by these structures can be expected to experience minor to moderate street and yard flooding during heavy rainfall that co-occurs with an average daily high tide.

A second tidal penetration assessment identified structures with bottom elevations below the 2015 king tide level, or 4.68' above NAVD88. A total of 334 stormwater structures, including 184 inlets and 150 outfalls, were identified as below this king tide elevation. Many of these structures are also located in the City's historic downtown waterfront area and associated with outfalls into the St. Marys River (Figure 4.7). However, neighborhoods that are drained by outfalls into Dark Entry Creek, including to the south of State Road 40 and just south of Colerain Dr., also show potential impacts from current king tides. Areas served by these structures can be expected to experience moderate to severe street and yard flooding during heavy rainfall that co-occurs with very high tides.

A third tidal penetration assessment identified structures vulnerable to 2065 king tide with *Intermediate-High* sea-level rise. The 2065 king tide under this scenario is 6.39' above NAVD88, or approximately 1.71' higher than a 2015 king tide. A total of 621 stormwater structures, including 358 inlets and 263 outfalls, were identified as below this elevation.



One of the Vinson Institute recommendations is to direct stormwater from rooftops into bioswales, vegetated greenspace, or capture and reuse devices like cisterns and rain barrels.

FIGURE 4.7: STORMWATER STRUCTURES WITH UNDERGROUND ELEVATION LESS THAN 2015 KING TIDE HEIGHT (4.68' ABOVE NAVD88), CITY OF ST. MARYS, GA.

Miles Consider the City's downtown drainage into the St. Marys River and many areas that drain directly into Dark Entry Creek show substantial impacts from annual king tides under this scenario. If this scenario does occur, the areas served by these structures could be expected to experience severe street and yard flooding, with some potential for minor flooding of low-lying structures, during heavy rainfall events that co-occur with very high tides.

Suggestions for Stormwater Adaptation

The results of this stormwater infrastructure assessment provide some objective confirmation of stakeholder observations about street-flooding issues in St. Marys, particularly within the City's historic downtown waterfront area. This is not surprising, as stresses and failures within municipal stormwater drainage systems are increasingly recognized as among the most chronic, complicated, and visible early consequences of sea-level rise across the country and throughout the world.⁴⁷

In 2016, faculty from the University of Georgia's Carl Vinson Institute of Government (Vinson Institute) worked with the City of St. Mary to develop the Downtown St. Mary Strategic Plan and Vision report, which outlines several steps that the City should consider for the purpose of reducing street flooding in the downtown area.⁴⁸

FIGURE 4.8: STORMWATER STRUC-TURES WITH UNDERGROUND ELEVATION LESS THAN 2065 KING TIDE HEIGHT WITH INTERMEDIATE HIGH SEA-LEVEL RISE (6.39' ABOVE NAVD88), CITY OF ST. MARYS, GA. The following provides a summary of key recommendations contained in the Vinson Institute report:

- Increased use and construction of "rain garden" bioswales that redirect stormwater from impervious streets and pipe infrastructure into vegetated greenspace areas. Vegetated areas will tend to slow down and reduce the volume of runoff that eventually enters into stormwater drainage systems, thus alleviating downstream flooding issues.
- Direct stormwater from building rooftops into bioswales, vegetated greenspace, or capture and reuse devices (e.g., rain barrels and cisterns), rather than into impervious surfaces (e.g., driveways and parking lots) that feed into street drainage systems. These practices also reduce the volume of runoff that enters into the stormwater drainage systems, which alleviates downstream flooding.
- Increase the tree canopy within developed areas of the City, including along streets. In addition to the beauty and water quality benefits associated with tree cover, the interception of rainfall by tree leaves is known to reduce the volume of that enters into stormwater systems.
- Conservation of undeveloped, low-lying properties along waterfront and marshfront areas of the City. Maintenance of low-lying areas as open space gives an opportunity for more sustainable stormwater management in the near-term, while also helping to alleviate longterm risks to property and people from increased tidal flooding.⁴⁹

While the above green infrastructure recommendations were developed specifically for the downtown area of St. Marys, the same principles and practices for runoff reduction can also be used in other areas of the City to help alleviate current and future stormwater flooding. However, it is likely that improved stormwater drainage, particularly under a condition of accelerated sea-level rise, would require pursuit of strategic and, in some cases, substantial upgrades to the City's existing hard, "gray" stormwater infrastructure. The following are three of the most common gray stormwater upgrades currently being pursued by coastal communities for the purpose of reducing stormwater and tidal flooding problems:

- Installation of backflow preventers on low-lying outfalls subject to tidal inundations. Backflow prevention devices include a variety of flap gates, check valves, and slide gates that are designed to keep tide water from entering into stormwater systems during high tide events. These devices are generally among the lowest cost upgrades for making a stormwater system more resistant to tidal flooding. However, backflow preventers do require periodic maintenance to ensure that they continue to function properly.⁵⁰ It is also important to note that while penetration of tidal water into stormwater systems is greatly lessened through use of backflow preventers, drainage of runoff during rainfall events will still be constrained by high tide events that submerge pipe outfalls.⁵¹
- Replacement of degraded and undersized underground pipes. The maximum discharge rate for a stormwater pipe system is controlled by factors that include the slope of the system, construction material, condition of pipes, and pipe diameter. Many urban stormwater systems, particularly those built decades ago, are characterized by undersized drainage pipes that are insufficient for handling large volumes of stormwater. These older drainage systems are very often also degraded by cracks, obstructions, and sedimentation, all of which further reduce drainage potential. Notably, much of the City's most vulnerable stormwater infrastructure is located in the historic downtown of St. Marys and was originally built in the early to mid-20th century. As the City moves to implement renovations within the historic downtown and waterfront, it is highly recommended that potential upgrades to the stormwater pipe infrastructure be included as a core scope within these projects.

It is expected that sea-level rise will cause a rise in water tables along the coastal zone, thereby reducing the rate of potential stormwater infiltration into increasingly saturated soils. Development of enhanced stormwater storage capacity in newly constructed retention and detention basins, particularly in more elevated areas. Over time, it is expected that sea-level rise will also cause a rise in water tables along the coastal zone, thereby reducing the rate of potential stormwater infiltration into increasingly saturated soils. Concerns about such issues have led some U.S. and European municipalities to consider "over-design" standards for new stormwater facilities in upland areas well above the water table. The primary idea behind such an over-design standard is that the excess storage capacity in these new facilities may be needed as a safety factor to ensure that very little runoff escapes into lower-lying coastal areas that are most vulnerable to flooding.⁵² Over the long-term, such facilities could also potentially be used as storage locations for excess water pumped from low-lying areas during rainfall events that co-occur with high tides.

The identification and design of particular projects to implement these suggested stormwater adaptation strategies will require engineering assessments and associated municipal resources that reach beyond the scope of this flood resiliency assessment. It is, however, suggested that the City of St. Marys begin considering a municipal stormwater utility fee structure for the purpose of generating funds dedicated to the maintenance and upgrade of the local drainage system. The University of Georgia has developed several publications and has other resources available for communities interested in studying the feasibility and appropriateness of a local stormwater utility.⁵³

- 21 Federal Emergency Management Agency. Flood Insurance Study Number 13039CV000A. Camden County, Georgia and Incorporated Areas. 2005. http://www.georgiadfirm.com/pdf/panels/13039cv000a.pdf. We note that the flood heights within the 2005 Flood Insurance Study provided the official basis for the Flood Insurance Rate Map in force in St. Marys and Camden County throughout the duration of this project. We also note, however, that FEMA has conducted extensive analyses to update the 2005 study, and that preliminary copies of the updated Flood Insurance Rate Map were released for public comment in 2016.
- 22 Supra note 14.
- 23 See, for example, Southeast Florida Regional Climate Change Compact Sea Level Rise Work Group. 2015. Unified Sea Level Rise Projection for Southeast Florida. http://www.southeastfloridaclimatecompact.org/wp-content/uploads/2015/10/2015-Compact-Unified-Sea-Level-Rise-Projection.pdf.
- 24 Nicholls, R.J. and A. Cazenave. 2010. Sea-level rise and its impact on coastal zones. Science 328:1517–1520.
- 25 Supra note 16.
- 26 See, for example, Hauer et al. (2016), supra note i; Hauer et al. (2015), supra note vii; Strauss, B.H., S. Kulp, and A. Levermann. 2015. Carbon choices determine US cities committed to futures below sea level. Proceeding of the National Academy of Sciences of the United States 112:13508–13513.
- 27 Sweet and Marra (2016), see supra note xvii.
- 28 Calculated using the United States Army Corps of Engineers Sea-Level Change Curve Calculator, Version 2015.46. http://www.corpsclimate.us/ccaceslcurves.cfm.
- 29 All values are calculated based upon a consistent 2015 king tide reference. This requires subtracting the assumed sea level rise between 1992 and 2015 before adding future sea-level rise respectively across all scenarios. The equational form for this correction is:

 $KT_{y, s} = KT_{2015} - SLR_{1992-2015, s} + SLR_{y, s}$; where

 $KT_{y,s} = King tide in year y under sea level rise scenario S$

KT₂₀₁₅ = King tide in 2015 (4.68')

SLR $_{1992-2015 S}$ = Sea level rise from 1992 to 2015 under sea level rise scenario S

 $SLR_{y,s}$ = Sea level rise from 1992 to year y under sea level rise scenario S

- 30 These additive changes represent a simple addition of sea level rise scenarios, using a 2015 baseline consistent with the king tide water levels in Table 4.2, to the Hurricane Matthew water level. Formal storm surge modeling of a Hurricane Matthew-type event, as based upon higher water levels associated with future sea-level rise, was outside of the scope and resources available for this project and therefore not performed for this analysis.
- 31 Data acquired from: https://www.usgs.gov/special-topic/hurricane-matthew
- 32 We caution that this analysis is only for general planning purposes and, due to limitations of the underlying elevation and road centerline datasets, is not of engineering or survey quality. Site-level elevation surveys and/or specific flood level observations are required to determine actual flooding vulnerability of identified road segments.
- 33 The listed minimum elevations represent ground elevation as extracted from a LIDAR-based digital elevation model, but do not necessarily reflect actual first floor elevation for any building or structure.
- 34 Eastern Research Group, Inc. 2013 What will adaptation cost? An economic framework for coastal community infrastructure. NOAA Coastal Services Center. https://coast.noaa.gov/data/digitalcoast/pdf/adaptation-report.pdf.
- 35 For parcels with multiple building footprints, the full appraised value was divided equally among the buildings for the purposes of the damage assessment.
- 36 Supra note 21.
- 37 United States Army Corps of Engineers. 2000. Economic Guidance Memorandum (EGM) 01–03, Generic Depth-Damage Relationships. https://planning.erdc.dren.mil/toolbox/library/EGMs/egm01-03.pdf. All buildings were assessed using the damage curve for one story, no basement structures. The original depth damage curve was adjusted upward by 2 feet based upon the assumption of a 2-foot elevation grade for the first floor of each structure.
- 38 Gersonius, B. R. Ashley, A. Pathirana, and C. Zevenbergen. 2012. Climate change uncertainty: Building flexibility into water and flood risk infrastructure. Climatic Change 116:411–423.
- 39 This NPV calculation "discounts" future damages based on the following function:

 $D_{NDV} = D_{t} / (1 + N)^{t}$, where

- D_{NDV} = Net Present Value Damage
- N = Discount rate (3.3%, or .033)
- t = Years since 2015
- D, = Damage calculation for year t, as based on 2015 assessed value
- 40 Equations and technical demonstration of the applied flood damage assessment method can be found in Chapter 3 of Eastern Research Group, Inc. (2013), supra note xxxiii, as well as Appendix VII of Evans et al. (2016), supra note ii.
- 41 It is important to note that the NPV flood vulnerability assessment, as summarized in Table 4.12, was conducted with available datasets that do have important limitations. Most notably, information about building-specific characteristics that could greatly mitigate flood damage — such as elevated first floors — was not available in a digital form. Inclusion of such site-specific information, which would require detailed surveys of structures in the floodplain, could potentially result in substantial changes — and likely reductions — in the cumulative damage estimates.
- 42 Beck, G.T. 2014 New York's new \$335 million storm-surge barrier will transform the lower east side. https://nextcity.org/daily/entry/ new-yorks-new-335-million-storm-surge-barrier-will-transform-the-lower-east
- 43 The estimated cost of a sea wall was derived from estimates originally published in Yohe, G., J. Neumann, P. Marshall, and H. Ameden. 1996. The economic cost of greenhouse-induced sea-level rise for developed property in the United States. Climatic Change 32:387–410. The standard estimate by Yohe et al. is \$750 per linear foot, with a high end estimate of \$4,000 per linear foot. Inflation adjustment from 1996 dollars to 2015 dollars results in a standard estimate of approximately \$1,150 per linear, with a high end estimate of approximately \$6,050 per linear foot.
- 44 Eastern Research Group, Inc. (2013), supra note xxxiii
- 45 These values per structure are simply calculated as D_{sup}/n, where
 - DSLR = Damages by sea level rise scenario, SLR, from Table 4.12
 - n = Number of structures in regulatory floodplain, which is 1,204
- 46 Highfield, W.E. and S.D. Brody. 2013. Evaluating the effectiveness of local mitigation activities in reducing flood losses. Natural Hazards Review 14:229–236.
- 47 Titus, J.G., C.Y. Kuo, M.J. Gibbs, and T.B. Laroche. 1989 Greenhouse effect, sea level rise, and coastal drainage systems. Journal of Water Resources Planning and Management 113:216–225.King, P.G., A.R. McGregor, and J.D. Whittet. 2016. Can California coastal managers plan for sea-level rise in a cost-effective way? Journal of Environmental Planning and Management 59:98–119.
- 48 Bivins, D., L.D. Holbrook, S. Pippin, K.M. Messich, T.C. Stancil, C. Stebbins, C. Riker, K DeVivo, and M. Bailey. 2016. Downtown St. Marys Strategic Vision and Plan. Athens: Carl Vinson Institute of Government. http://www.stmarysga.gov/St.%20Marys%20 Report%20FINAL.pdf.
- 49 Runoff reduction and water quality benefits from these green infrastructure practices are described in great detail by: Center for Watershed Protection. 2009. Coastal Stormwater Supplement to the Georgia Stormwater Manual. http://documents.atlantaregional. com/gastormwater/Georgia-CSS-Final-Apr-09.pdf.
- 50 New Haven (CT) City Plan Department. 2010. Natural Hazard Mitigation Plan Update. http://www.cityofnewhaven.com/cityplan/pdfs/ PlanningPrograms/Final%20NH-HMP[1]-%20latest%20version.pdf.
- 51 Dent, S. and S. Deslauriers. 2013. Master planning collection systems in a time of uncertainty: Climate change, adaptive management, and defining new levels of service. Proceedings of the Water Environment Federation 15:322–336.
- 52 Semadeni-Davies, A., C. Hernebring, G. Svensson, and L.G. Gustafsson. 2008. The impacts of climate change and urbanization and drainage in Helsinborg, Sweden: Suburban stormwater. Journal of Hydrology 350:114–125. Bloetscher, F., B.N. Heimlich, and T. Romah. 2011. Counteracting the effects of sea level rise in Southeast Florida. Journal of Environmental Science and Engineering 5:1507–1525. Bird, J.M. M. Tobin, T. McGowan, and M. Abbott. 2015. A Research Paper Reviewing Issues and Unintended Consequences related to Raising Minimum Building Finish Floor Elevations. City of Miami Beach, FL.
- 53 Smith, J. 2006. Stormwater Utilities in Georgia. University of Georgia School of Law. http://digitalcommons.law.uga.edu/cgi/viewcontent.cgi?article=1013&context=landuse. Carter, T.L. 2008. Stormwater Utility Handbook: A Step-by-Step Guide to Establishing a Utility in Coastal Georgia. https://epd.georgia.gov/sites/epd.georgia.gov/files/related_files/site_page/Coastal_Stormwater_Utility_ Handbook_2008.pdf.

CHAPTER 5:

The Community Rating System (CRS) is a voluntary Federal Emergency Management Agency (FEMA) program that rewards communities for exceeding minimum floodplain management standards, thereby improving public safety and the economic stability of the community. It can be an efficient and cost-effective way for local governments to address the rising costs of flood insurance in the community, while simultaneously building resilience, minimizing damage to people and property and speeding up the recovery process.

Local communities gain points in the CRS program by improving their preparation and response to flooding issues through developing and documenting public information activities, improved mapping capacity, adoption of enhanced floodplain regulations, implementation of flood damage reduction mechanisms, and enhanced warning and response procedures. The CRS has three goals: 1) reduce and avoid flood damage to insurable properties, 2) strengthen and support the insurable aspects of the National Flood Insurance Program, and 3) foster comprehensive floodplain management.

When the St. Marys Flood Resiliency Project began in 2013, the City of St. Marys was not a participant in the CRS. Any community that does not participate is automatically classified as a 10 on the CRS scale, earning zero reductions in flood insurance premiums for policyholders. One of the core goals of the St. Marys Flood Resiliency Project was to assist the City in joining the CRS program.

RISING COST OF FLOOD INSURANCE

Flooding has been, and continues to be, a serious risk in the United States — so serious that most insurance companies have specifically excluded flood damage from homeowners insurance. To address the need, in 1968 the U.S. Congress established the National Flood Insurance Program (NFIP). It enabled property owners in participating communities to purchase flood insurance, if the community had adopted floodplain management ordinances and minimum standards for new construction. However, owners of existing homes and businesses did not have to rebuild to the higher standards, and many received subsidized rates that did not reflect their property's true risk.

Fortuitously, the timing of the St. Marys Flood Resiliency Project coincided with drastic changes that were taking place in flood insurance policy at the national level. Due to unprecedented insurance claims made to FEMA during the aftermath of Hurricane Katrina and Super Storm Sandy, the NFIP was billions of dollars in debt and Congress sought to take action to ensure the solvency of the flood insurance program. The Biggert-Waters Flood Insurance Reform Act of 2012 was passed by Congress and signed into law by the President. The consequences of suddenly imposing actuarial flooding insurance rates within the very next policy cycle led to some residents facing mandatory insurance costs that exceeded their mortgages, compromised their ability to sell their property and exacerbated foreclosures. This produced an outcry from coastal residents affected by the policy changes and a demand from lawmakers for a deeper understanding of flooding issues.

In response, in March of 2013, Georgia Sea Grant conducted its first Community Rating System workshop in Brunswick in partnership with the Georgia Environmental Protection Division Flood Plain Unit, the FEMA insurance and elevation certificate specialist, the FEMA outreach specialist, the Insurance Services Office agent and the Department of Natural Resources Coastal Hazards specialist. Over 50 people representing 17 coastal communities attended this workshop. A post-workshop evaluation identified CRs as the program which could offset increasing insurance costs, and indicated a strong need for coastal CRs training and outreach.

In the fall of 2013, then Congressman Jack Kingston reached out to Georgia Sea Grant staff in search of guidance and education on the issue of flooding vulnerability and economic consequences. Over the next several months, Georgia Sea Grant staff worked closely with the Congressman's office, informing him and his staff about coastal flooding and vulnerability. In 2014, the Homeowner Flood Insurance Affordability Act became law, thus modifying and repealing certain provisions in the previous legislation, including a gradual increase in premiums over a five-year period. Even with the implementation of this act, coastal residents have seen increased premiums, higher policy fees and added mandatory surcharges.

CRS in Coastal Georgia

As of October 1, 2016, 16 cities and counties in coastal Georgia were active CRS participants. Due in part to the efforts of Georgia Sea Grant and its partners, several participating communities in coastal Georgia have improved their scores since 2014, resulting in additional savings for property owners.

COMMUNITY RATING SYSTEM (CRS) IN ST. MARYS

One of the most significant achievements of this project has been the successful entry of St. Marys into the CRS at a rating of seven, thus resulting in a 15 percent reduction in flood insurance premiums for residents in the special flood hazard area. Not only has the City been rewarded for requiring higher minimum standards for flood preparedness, citizens have saved over \$87,000 in annual flood insurance premiums.

Earning CRS Points in St. Marys

- Georgia Sea Grant collaborated with the City of St. Marys staff and Georgia DNR to document and calculate the amount of open space within the city boundaries. Points are awarded for the amount of open space areas that are preserved, or in the process of becoming preserved, to their natural state.
- The City is requiring that all new construction have two feet of freeboard. Freeboard is elevating the lowest floor of a building, in this case houses, by a set additional height above the National Flood Insurance Program's minimum height requirements. This will further protect homes from damage due to flooding events.
- Georgia Sea Grant assisted in establishing a flood reference section in the St. Marys and Camden County public libraries. Making required FEMA materials on flood protection and other locally pertinent materials available at public libraries not only helps communities earn CRs credit, but also helps to ensure public safety, minimize property damage and assist recovery efforts related to flooding.

Georgia Sea Grant also helped by creating maps and diagrams detailing how sealevel rise might impact the city. It additionally assisted in educating residents about their flood risk, through hosting public Town Hall meetings and other outreach opportunities. Georgia Sea Grant's efforts led to further research in downtown St. Marys to plan for how the historic district might adapt to current and future flooding.

"If your community is considering entering into the CRS Program, the Sea Grant staff can provide the knowledge and experience to assist your community in the CRS application.Their assistance was invaluable."

MICHELE WOOD, ST. MARYS FLOODPLAIN MANAGER

CRS TRAINING

As previously mentioned, Georgia Sea Grant and its partners provided diverse educational opportunities for local decision-makers and community members throughout the project cycle, using the latest research and on-the-ground observations. The organizations also provided intensive trainings on CRS, offering technical expertise and guidance to increase understanding and participation in the National Flood Insurance Program (NFIP) among local governments on the coast.

- National Flood Insurance Program's Community Rating System Workshop: A Step-by-Step Guide for Coastal Governments: March 1, 2013 in Brunswick, Georgia Over 30 coastal government officials, staff and other interested parties gathered to learn more about the CRS program and its benefits to communities.
 - Preliminary Release of the New Coastal Floodplain Maps: August 19, 2015 in Brunswick, Georgia FEMA and state floodplain managers presented engineering and mapping data to 60 officials from Glynn, McIntosh Camden and Long Counties, outlining the timeframe in which the new flood maps will be released to the public. Representatives from Senator Johnny Isakson's office and Congressman Buddy Carter's office were also present.
- Beyond the Why and Getting to How: Earning CRS Credits for Open Space, Regulatory Standards and Voluntary Property Acquisition Programs: August 28, 2014 in Savannah, Georgia

Georgia Sea Grant partnered with the UGA Carl Vinson Institute of Government to host a flooding policy and planning workshop for over 200 people, focused on best practices and tips for success in joining or complying with the CRS program.

FEMA Elevation Certificate Workshop: September 17, 2015 in Brunswick, Georgia This training was can due to d for surrousing angine and do d

This training was conducted for surveyors, engineers, floodplain administrators and municipal and county officials.

FEMA Floodplain Managers Training: December 7–11, 2015 in Brunswick, Georgia

FEMA's training on managing floodplain development usually occurs in Maryland; however, Georgia Sea Grant helped offer this course at its UGA Marine Extension facility in Brunswick, allowing twenty local government staff from across the state to more accessibly acquire their Floodplain Management Certification.

NETWORK BUILDING

The project team also helped build a coalition of coastal communities to tackle the challenges of flooding, so that cities and counties with greater experience and capacity can assist smaller or more rural communities. This included organizing forums where scientists, practitioners and local government staff could share lessons learned with one another, as well as challenges and opportunities for earning points in CRS.

Throughout the project period, Georgia Sea Grant helped establish the following learning networks:

- The COASTAL GEORGIA CRS USERS GROUP expanded to include Camden County and St. Marys by offering to rotate the location of its meeting among the participating communities.
- One benefit of this strengthened support between floodplain managers is a new collaboration between Camden County and St. Marys to create THE STATE'S FIRST PROGRAM FOR PUBLIC INFORMATION (PPI), an outreach collaboration to increase awareness of flooding and coastal hazards.
- The GEORGIA COASTAL HAZARDS COMMUNITY OF PRACTICE provides opportunities to share activities best management practices for coastal climate-related projects and FEMA's Community Rating System.

Community Flood Information Library

To ensure public safety, minimize property damage and assist recovery efforts related to flooding, FEMA recommends that all communities close to flood-prone rivers and coasts make information about floods and flood insurance available to their citizens. Not only is this information invaluable for public safety, but making these materials available at the public library can help communities earn credit and reduce the cost of flood insurance under the Federal Emergency Management Agency (FEMA) Community Rating System.

FEMA requires a group of nine publications to be available at the local library for a community to receive CRS credit under the Flood Protection Library (LIB) element. FEMA also provides credit for making information specifically related to floods and flood plains in the local area available to the public. These are credited under the Locally Pertinent Documents (LPD) element. Listed below are the required FEMA materials, followed by a list of Locally Pertinent Documents with examples for coastal Georgia. These materials have been provided by public libraries in the City of St. Marys and Camden County and are located within their flood information sections.

FEMA provides hard copies of many of their documents to community libraries free of charge. Information on preparing for floods, flood insurance and flood recovery also can be found by following the links below.

FEMA Required Materials:

- Community Rating System Coordinator's Manual
- Above the Flood: Elevating Your Flood Prone House, FEMA-347 (2000)
- Answers to Questions About the National Flood Insurance Program, F-084 (2011)
- Coastal Construction Manual, FEMA-P-55, (2011)
- **5** Elevated Residential Structures, FEMA-54 (1984)
- Protecting Manufactured Homes from Floods and Other Hazards, FEMA P-85 (2009)
- Mitigation of Flood and Erosion Damage to Residential Buildings in Coastal Areas, FEMA-257 (1994)
- ⁸ Protecting Building Utilities From Flood Damage, FEMA-P-348 (1999)
- 9 Protecting Floodplain Resources, FEMA-268 (1996)
- Reducing Damage from Localized Flooding, FEMA 511 (2005)

Locally Pertinent Documents:

- Community Handbook on Floodplain Management
- 2 Georgia Floodplain Management
- 6 Community Floodplain Management Ordinance
- Invironmental Organization's Guide to Habitat
- **6** Community FIRM
- 6 Army Corps of Engineers Reconnaissance Report
- Community Flood Insurance Study
- ⁸ County's Floodplain Management or Hazard Mitigation Plan
- 9 Local Resource Management Plans Related to Floodplains

BOBBY MARR Public Works Director

TELEPHONE 912/882-4415 FAX: 912/673-6681

DEPARTMENT OF PUBLIC WORKS 418 OSBORNE STREET * ST. MARYS, GEORGIA 31558

DRAINAGE SYSTEM MAINTENANCE STANDARD OPERATING PROCEDURE JUNE 2015

 Objective: This Standard Operating Procedure (SOP) specifies responsibilities and procedures for inspecting and cleaning the streams, creeks, ditches, and drainage easements in the City of St. Marys, Georgia.

2. Responsibilities:

a. The Director of the Public Works Department is responsible for the administration of this SOP. The area supervisors shall inspect the major streams, creeks, ditches, and drainage easements periodically and ensure that they are cleaned in accordance with this SOP.

b. The Director of Public Works is responsible for implementing the Stormwater Management Plan adopted by the City of St. Marys (June 2008) and overseeing the improvements recommended by the Plan as funding becomes available.

c. Private property owners are responsible for maintaining the streams, creeks, and ditches on their properties which do not lie within drainage easements that have been dedicated to the City of St. Marys, GA.

3. Jurisdiction: This SOP covers all of the incorporated areas of the City of St. Marys, GA.

4. Identification of Problems:

a. The Director of Public Works or area supervisors shall inspect all major outfall ditches and major drainage easements once a year, at a minimum. This inspection will be conducted before the start of the hurricane season (June 1).

b. Inspections shall consist of walking the length of each outfall ditch and a visual check through all culverts.

c. The Director of Public Works or area supervisors shall complete a work order after each inspection. All work orders shall be kept in an appropriate file.

d. The Director of Public Works or area supervisors shall inspect all complaints submitted by residents, co-workers, or other offices. Such complaints and the subsequent action taken by the Public Works Department shall be recorded on a work order. The

Director of Public Works or area supervisor shall ensure that an inspection is conducted and the findings provided to the person submitting the complaint within one week after the inspection is conducted.

e. If a problem is found, the work order shall be forwarded to the appropriate area supervisor. The work order shall be recorded and maintained in accordance with the Public Works standard procedures. If the problem is on private property, a letter shall also be sent to the owner.

5. Maintenance:

a. There are four types of maintenance problems:

1) Trash: human-made objects, such as garbage, shopping carts, tires, lumber, furniture, and appliances. Animal carcasses are also included as trash.

2) Minor problem: vegetation growth, tree limbs, and other "naturally" occurring debris. Sedimentation along dirt roads is also included.

3) Obstruction: fallen tree, culvert damage, large appliance, etc., that, by itself, obstructs the flow of the ditch, inlet or outlet.

4) Structural project: bridge or culvert replacement, bank stabilization, dredging, or other major project.

b. Maintenance duties:

1) On public property: The Director of Public Works or area supervisors shall ensure that trash and minor problems are removed at the earliest convenient time. Obstructions shall be removed within two working days of being reported.

2) Structural projects may require budget approval by the City Manager or the St. Marys City Council and, sometimes, a separate permit from the Department of Natural Resources or the Army Corps of Engineers. If necessary, a drainage maintenance easement shall be obtained from all affected property owners. Structural projects beyond the scope of public works shall be advertised for bid and scheduled in the same manner as other contracted St. Marys projects.

3) Upon completion of a maintenance project, the area supervisor shall complete the corrective work order and shall be recorded and maintained in accordance with the Public Works procedures.

c. Maintenance on private property and gated subdivisions:

1) Property owners are responsible for maintaining the streams, ditches, swales, storm sewer inlets, and retention basins on their properties which do not lie within drainage easements that have been dedicated to the City of St. Marys, GA.

2) Trash, minor problems, and obstructions shall be reported to the owner by the area supervisor or other representative from the Public Works Department.

CITY OF ST. MARYS 418 OSBORNE STREET ST. MARYS, GEORGIA 31558 PLANNING AND ZONING DEPARTMENT TELEPHONE: 912-510-4032 FAX: 912-510-4014

GENERAL ADMINISTRATION: ELEVATION CERTIFICATE PROCEDURES

I. PURPOSE AND SCOPE

A. To formalize existing procedures for reviewing and processing Elevation Certificates (EC).

II. RESPONSIBILITIES AND CONSIDERATIONS

- A. It is the responsibility of the Floodplain Manager or designee to review Elevation Certificates in accordance with this SOP and applicable FEMA/NFIP requirements.
- B. Elevation Certificates are required for all new construction and substantial improvements to structures (more than 50% of the value in the past five years) when the property is in the Special Flood Hazard Area (SFHA).
- C. No Certificates of Occupancy or Completion shall be issued without an acceptable Elevation Certificate.
- D. Additional Guidance on Elevation Certificates can be found in the following publications, which are maintained in the Floodplain Manager's Office:
- a. Elevation Certificates Checklist
- b. Floodplain Management Ordinance
- c. The 2012 Georgia Building Code

III. PROCEDURE

- 1) Pre-Elevation Certificates are including with the submittal of the building permit. Post-Elevation Certificates are submitted prior to the issuance of a Certificate of Occupancy.
- The Elevation Certificate shall be specifically reviewed against the attached CRS EC Checklist.
- 3) All required fields as highlighted on the EC Checklist must be completed with correct information.
- 4) If deficiencies are found, make a copy and mark up those areas that need to be corrected with notes and provide a copy to the applicant for their correction and re-submittal.
- 5) If the Elevation Certificate is found to be in compliance with the EC Checklist and the Elevation Certificate demonstrates compliance with all applicable policies and/or permit conditions, the following steps shall be accomplished:
 - a. Scan the Elevation Certificate and save it to the appropriate folder.
 - b. Staple the Elevation Certficate to the associated Building Permit and place in the associated permit file folder.

CRS CHECKLIST FOR THE 2006, 2009, AND 2012 FEMA ELEVATION CERTIFICATE FORMS

SECTION A - PROPERTY INFORMATION

- A2 and A3 Complete street address or property description. In either case, the city, state, and zip code must be listed.
- A6 Photographs: Photographs are not required for CRS credit. However, they are required for writing a flood insurance policy and they can be very helpful for compliance records.
- A7 Building diagram number.
- A8 a), b), and c) Enclosure and crawl space information for buildings that are diagram 6, 7, 8, or 9.
- A9 a), b), and c) Attached garage information. If there is no attaché garage, enter "N/A" in all three spaces. If there is an attached garage and there are no openings, the correct entry is "zero," even if the garage is above the BFE.
- A8 and A9 If the square footage of the crawlspace or garage is larger than the square inches of the openings AND "(d) Engineered flood openings" is checked "yes," then there must be a certification by a registered design professional or a copy of the ICC Evaluation Service report.

SECTION B - FLOOD INSURANCE RATE MAP (FIRM) INFORMATION

- B1 NFIP community name/community number.
- B4 Map AND panel number.
- **B5** Panel number suffix. If the property is in an area revised by a LOMR, then B4, B5, and B7 must all be completed based on the LOMR.
- B7 FIRM panel effective/revised date.
- B8 Flood zone(s) in which the building is located. B9 Base flood elevation(s).
- B10 The source of the base flood elevation data or base flood depth entered in B9.
- B11 The elevation datum used for the base flood elevation in B9.
- B12 Whether the building is located in a Coastal Barrier Resources System area or Otherwise Protected Area.

SECTION C - BUILDING ELEVATION INFORMATION (when a survey is required)

- C1 Basis for building elevations: Note: "Finished construction" must be checked unless the building is still under construction. The ISO/CRS Specialist will not review Elevation Certificates for buildings still under construction, unless requested to by the community.
- C2 Elevations. The benchmark utilized and vertical datum entries must be completed. Items a) through g) must have an entry. Elevation items a), f), and g) must be recorded on every certificate. If an item does not apply, enter "N/A" in the fields where no data are being supplied. Items b) and c) must be completed with an elevation if they are applicable and if that letter appears on the diagram on

pages 7–9 of the instructions. If there is an attached garage, an elevation must be entered for item d); otherwise the entry is "N/A." If there is machinery and/or equipment that service the building, an elevation must be entered for item e), otherwise the entry is "N/A."

SECTION D - CERTIFICATION BY A REGISTERED DESIGN PROFESSIONAL

Certifier's name and license number Certifier's signature Date

If there is a signature and/or date in the box, there does not have to be a separate signature or date on the line.

- SECTION E BUILDING ELEVATION INFORMATION (when a survey is not required in a Zone AO or a Zone A without a base flood elevation)
- E1 a) and b) Enter the difference between the top of the bottom floor and the highest and lowest adjacent grade.
- E2 For Building Diagrams 6–9 with openings, enter the difference between the top of the next higher floor and the highest adjacent grade.
- E3 Enter the difference between the top of the garage slab and the highest adjacent grade.
- E4 Enter the difference between the top of the platform for machinery or equipment and the highest adjacent grade.
- E5 Zone AO (only) Elevation of bottom floor complies with the ordinance (if there is no base flood depth provided).

Note: If Section E is used, then Sections F or G must be completed.

<u>SECTION F - PROPERTY OWNER (OR OWNER'S REPRESENTATIVE) CERTIFICATION</u> This section is used if Section E is completed by the owner or owner's representative. If used, this section must include the property owner's or representative's name in the first line and the signature in the third line.

SECTION G - COMMUNITY INFORMATION If G1 or G2 is checked, then the first and third lines after G10 (the local official's name and signature) must be completed.

Note: If a local official authorized by law to complete an Elevation Certificate fills out ALL the information (including elevation data), then G8, G9, and the signature block must be completed.

FEDERAL EMERGENCY MANAG National Flood Insurance Program	LAND SECURITY SEMENT AGENCY	ELEVATION CE IMPORTANT: Follow the instru-	RTIFICATE uctions on pages 1–9.	E	MB No. 1660-0008 xpiration Date: July 31, 2015 beck Date of Certificate
		SECTION A - PROPERT	Y INFORMATION	F	OR INSURANCE COMPANY USE
A1. Building Owner's Nam	e	CPS FC Ch	ockligt	P	olicy Number:
A2 Ruilding Street Addres	e (including Ant Uni	t Suite and/or Bldg No.) or PO R			ompany NAIC Number:
AZ. Building Street Addres	sa (morading Aper, on	t, oute, and of oldg. No.) of i.e. f		ľ	
City Either A2	or A3 must	be completed	State	ZIF	² Code
A3. Property Description (Lot and Block Numbe	ers, Tax Parcel Number, Legal Desc	ription, etc.)		
AA Building Use (e.g. Re	sidential Non-Reside	ntial Addition Accessory etc.)			
A5. Latitude/Longitude: L	at	Long		Horizontal Da	atum: 🗌 NAD 1927 🗌 NAD 1983
A6. Attach at least 2 phot	ographs of the building	ng if the Certificate is being used t	to obtain flood insurance	в.	
A8. For a building with a c	rawlspace or enclosu	ire(s):	A9. For a building	with an atta	thed garage: If sq provided
a) Square footage of	crawlspace or enclos	sure(s)sq f	t a) Square fo	otage of atta	ched garage check C2(d) sq ft
b) No. of permanent enclosure(s) within	flood openings in the 1.0 foot above adja	crawlspace or	b) Number of within 1.0	of permanent of foot above a	flood openings in the attached garage
c) Total net area of fl	ood openings in A8.b) sq i	n c) Total net	area of flood	openings in A9.b sq in
d) Engineered flood (openings? 🗌 Yes	🗆 No	d) Engineer	ed flood open	ings? 🗌 Yes 🗌 No
	SECTION	B - FLOOD INSURANCE RA	TE MAP (FIRM) IN	ORMATION	4
B1. NFIP Community Name	e & Community Numb	B2. County	Name Chatham		B3. State
Town of Thunde	B5. Suffix R6	FIRM Index Date B7 FIRM P	anel Effective/ B8 F	lood Zone(s)	B9, Base Flood Elevation(s) (Zone
5100 & panel #162, 166,		Revised	d Date	VAE or V	AO, use base flood depth)
or 170	F	09/26/2008 09/26/	/2008	IY AL OF A	Only 11, 12, or 13
B10. Indicate the source of	f the Base Flood Elev	ation (BFE) data or base flood dep	th entered in Item B9:		
B11 Indicate elevation dat	um used for BEE in It	rem B9 NGVD 1929		ther/Source:	
B12. Is the building located	in a Coastal Barrier	Resources System (CBRS) area o	r Otherwise Protected A	rea (OPA)?	Yes No
Designation Date:	//	CBRS OPA			Always marked "No"
C1. Building elevations ar	SECTION C	Construction Drawings*	FORMATION (SURVE Building Under Construct	EY REQUIR	ED) Finished Construction
C1. Building elevations ar *A new Elevation Cerl C2. Elevations – Zones A: C2.a-h below accord	SECTION C e based on: Lificate will be require L-A30, AE, AH, A (with ng to the building dia	C - BUILDING ELEVATION INF Construction Drawings* d when construction of the buildin h BFE), VE, V1-V30, V (with BFE), A gram specified in Item A7. In Puer	Building Under Construct g is complete. RR, AR/A, AR/AE, AR/A1 to Rico only, enter meter	EY REQUIRI ction* [L-A30, AR/AH ers.	ED) Finished Construction , AR/AO. Complete Items
 C1. Building elevations ar *A new Elevation Cerr C2. Elevations – Zones A C2.a-h below accordi Benchmark Utilized: 	SECTION C e based on: Lificate will be require L–A30, AE, AH, A (with ng to the building dia	C - BUILDING ELEVATION INF Construction Drawings* ad when construction of the buildin h BFE), VE, V1–V30, V (with BFE), A gram specified in Item A7. In Puer Ver	FORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter meter rtical Datum:	EY REQUIRI ction* [L-A30, AR/AH ers.	Thished Construction AR/AO. Complete Items
C1. Building elevations ar *A new Elevation Cert C2. Elevations – Zones A: C2.a-h below accordi Benchmark Utilized:_ Indicate elevation dat Datum used for build	SECTION C e based on: Lificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the elevel ng elevations must b	C – BUILDING ELEVATION INF Construction Drawings*	FORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter meter rtical Datum:	EY REQUIRI ction* [L-A30, AR/AH ers. NAVD 1988 [
C1. Building elevations ar *A new Elevation Cert C2. Elevations – Zones A: C2.a-h below accordi Benchmark Utilized: Indicate elevation dat Datum used for buildi	SECTION C e based on: Lificate will be require L-A30, AE, AH, A (witt ng to the building dia um used for the eleva ng elevations must b	C – BUILDING ELEVATION INF Construction Drawings*	FORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter meter rtical Datum: W. NGVD 1929 N FE.	EY REQUIRI btion* [L-A30, AR/AH ers. VAVD 1988 [Check the me	AR/A0. Complete Items Other/Source: asurement used.
 C1. Building elevations ar *A new Elevation Cerl C2. Elevations – Zones A: C2.a-h below accordi Benchmark Utilized:	SECTION C e based on: Lificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the eleva ng elevations must b r (including basement ther floor	C – BUILDING ELEVATION INF Construction Drawings* d when construction of the buildin h BFE), VE, V1–V30, V (with BFE), A gram specified in Item A7. In Puer Ver ations in items a) through h) below be the same as that used for the B t, crawlspace, or enclosure floor)	FORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter meter tical Datum; 	EY REQUIRI ction* [L-A30, AR/AH ers. VAVD 1988 [Check the me feet feet	
 C1. Building elevations ar *A new Elevation Cerf C2. Elevations – Zones A: C2.a-h below accordi Benchmark Utilized: _ Indicate elevation dat Datum used for buildi a) Top of bottom floo b) Top of the next hig c) Bottom of the lower 	SECTION C e based on: Lificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the eleva ng elevations must b r (including basement ther floor ast horizontal structure	C - BUILDING ELEVATION INF Construction Drawings* Gonstruction of the buildin h BFE), VE, V1–V30, V (with BFE), A agram specified in Item A7. In Puer Ver ations in items a) through h) below be the same as that used for the B t, crawlspace, or enclosure floor) ral member (V Zones only)	FORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter mete (tical Datum) (C) NGVD 1929 () FE. () (C) NGVD 1929 () (FE. () (C) (C) (C) (C) (C) (C) (C) (C) (C) (C)	EY REQUIRI ction* [L-A30, AR/AH ers. NAVD 1988 [Check the me feet feet feet feet	
 C1. Building elevations ar *A new Elevation Cer C2. Elevations – Zones A: C2.a-h below accordi Benchmark Utilized: _ Indicate elevation dat Datum used for buildi a) Top of bottom floo b) Top of the next hig c) Bottom of the lowe d) Attached garage (t) 	SECTION C e based on: tificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the elevi- ng elevations must b r (including basement gher floor est horizontal structur op of slab)	BUILDING ELEVATION INF Construction Drawings* d when construction of the buildin h BFE), VE, V1–V30, V (with BFE), A agram specified in Item A7. In Puer Ver ations in items a) through h) below be the same as that used for the B t, crawlspace, or enclosure floor) ral member (V Zones only)	FORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter meter (tical Datum) (I) NGVD 1929 [] [] FE. () (I) NGVD 1929 [] (I) NGVD 1920 []	EY REQUIRI ottion* [L-A30, AR/AH ers. NAVD 1988 [Check the me [feet [feet [feet [feet [feet]	
 C1. Building elevations ar *A new Elevation Cer C2. Elevations – Zones A: C2.a-h below accordi Benchmark Utilized:	SECTION C e based on: tificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the eleving elevations must b r (including basement ther floor est horizontal structur op of slab) of machinery or equip	C – BUILDING ELEVATION INF Construction Drawings* d when construction of the building h BFE), VE, V1–V30, V (with BFE), A logram specified in Item A7. In Puer Ver ations in items a) through h) below he the same as that used for the B t, crawlspace, or enclosure floor) ral member (V Zones only) ment servicing the building	FORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter meter (tical Datum: 	EY REQUIRI ction* [L-A30, AR/AH ers. NAVD 1988 [Check the me [feet [feet [feet [feet [feet [feet	
 C1. Building elevations ar *A new Elevation Cer C2. Elevations – Zones A: C2.a-h below accordi Benchmark Utilized: _ Indicate elevation dat Datum used for buildi a) Top of bottom floo b) Top of the next hig c) Bottom of the lowed d) Attached garage (t) e) Lowest elevation of (Describe type of the next high of the lowed) 	SECTION C e based on: tificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the eleving elevations must b r (including basement ther floor ast horizontal structur op of slab) of machinery or equip equipment and location	C – BUILDING ELEVATION INF Construction Drawings* d when construction of the building h BFE), VE, V1–V30, V (with BFE), A agram specified in Item A7. In Puer Ver ations in items a) through h) below be the same as that used for the B t, crawispace, or enclosure floor) ral member (V Zones only) ment servicing the building on in Comments) building (LSC)	FORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter meter rtical Datum: 	EY REQUIRI ottion* [L-A30, AR/AH ers. VAVD 1988 [Check the me [feet [feet [feet [feet [feet]] feet	
 C1. Building elevations ar *A new Elevation Cer C2. Elevations – Zones A C2.a–h below accordi Benchmark Utilized:	SECTION C e based on: tificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the eleving elevations must b r (including basement gher floor est horizontal structur op of slab) of machinery or equip equipment and location inished) grade next to finished) grade next to	C - BUILDING ELEVATION INF Construction Drawings* d when construction of the buildin h BFE), VE, V1–V30, V (with BFE), A agram specified in Item A7. In Puer ver ations in items a) through h) below be the same as that used for the B t, orawlspace, or enclosure floor) ral member (V Zones only) ment servicing the building on in Comments) o building (LAG) to building (HAG)	FORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Ricc only, enter meter rtical Datum: V. INGVD 1929 I	EY REQUIRI ction* [L-A30, AR/AH ers. VAVD 1988 [Check the me feet feet feet feet feet feet feet fe	
 C1. Building elevations ar *A new Elevation Cer C2. Elevations – Zones A: C2.a-h below accordi Benchmark Utilized:	SECTION C e based on: tificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the eleving elevations must b r (including basement gher floor) ast horizontal structur op of slab) of machinery or equip aquipment and location finished) grade next to finished) grade next to	BUILDING ELEVATION INF Construction Drawings* d when construction of the buildin h BFE), VE, V1–V30, V (with BFE), A gram specified in Item A7. In Puer	FORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Ricc only, enter meter rtical Datum: V. INGVD 1929 I	EY REQUIRI ction* [L-A30, AR/AH ers. VAVD 1988 [Check the me feet feet feet feet feet feet feet fe	
 C1. Building elevations ar *A new Elevation Ceri C2. Elevations – Zones A: C2.a-h below accordi Benchmark Utilized:	SECTION C e based on: Lificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the elev- ng elevations must b r (including basement gher floor ast horizontal structur op of slab)) of machinery or equip aquipment and locatiti inished) grade next to finished) grade next to	BUILDING ELEVATION INF Construction Drawings* d when construction of the buildin h BFE), VE, V1–V30, V (with BFE), A agram specified in Item A7. In Puer ver ations in items a) through h) below be the same as that used for the B t, crawlspace, or enclosure floor) ral member (V Zones only) ment servicing the building on in Comments) o building (LAG) to building (HAG) tion of deck or stairs, including	FORMATION (SURVE Building Under Constructing is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter meter trical Datum: v. INGVD 1929 IFE.	EY REQUIRI ction* [L-A30, AR/AH ers. VAVD 1988 [Check the me feet feet feet feet feet feet feet fe	
 C1. Building elevations ar *A new Elevation Ceri C2. Elevations – Zones A: C2.a-h below accordi Benchmark Utilized:_ Indicate elevation dat Datum used for buildi a) Top of bottom floo b) Top of the next hig c) Bottom of the lowed d) Attached garage (fi e) Lowest elevation of (Describe type of eff) f) Lowest adjacent (fi g) Highest adjacent g structural support 	SECTION C e based on: lificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the elev- ng elevations must b r (including basement ther floor est horizontal structur op of slab)) of machinery or equip equipment and locatit inished) grade next to finished) grade next to rade at lowest elevat		FORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter meter trical Datum: y, \[] NGVD 1929 \[] N FE. 	AVD 1988 [Check the me feet feet feet feet feet feet feet fe	
 C1. Building elevations ar *A new Elevation Cer C2. Elevations – Zones A: C2.a–h below accordi Benchmark Utilized:_ Indicate elevation dat Datum used for buildi a) Top of bottom floo b) Top of the next hig c) Bottom of the lowed d) Attached garage (Describe type of elevation of (Describe type of elevation of Lowest adjacent (find) h) Lowest adjacent (find) h) Lowest adjacent g structural support 	SECTION C e based on: Lificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the elevi- ng elevations must b r (including basement gher floor est horizontal structur op of slab) of machinery or equip equipment and locatit inished) grade next to finished) grade next to finished) grade next to sECTION gned and sealed by a	A BUILDING ELEVATION INF Construction Drawings* d when construction of the buildin h BFE), VE, V1–V30, V (with BFE), A agram specified in Item A7. In Puer Ver ations in items a) through h) below he the same as that used for the B t, crawispace, or enclosure floor) ral member (V Zones only) ment servicing the building on in Comments) o building (LAG) to building (HAG) tion of deck or stairs, including a land surveyor, engineer, or archite	CORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter meter (cical Datum) y. \[] NGVD 1929 \[] N FE. 	AVD 1988 [Check the me feet feet feet feet feet feet feet fe	
 C1. Building elevations ar *A new Elevation Ceri C2. Elevations – Zones A: C2.a-h below accordi Benchmark Utilized:	SECTION C e based on: Lificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the eleving ng elevations must b r (including basement gher floor east horizontal structur op of slab) of machinery or equip gaupment and location inished) grade next to finished) grade next to finished) grade next to finished) grade next to section SECTION gned and sealed by a e information on this statement may be not	A BUILDING ELEVATION INF Construction Drawings* d when construction of the buildin h BFE), VE, V1–V30, V (with BFE), A agram specified in Item A7. In Puer Ver ations in items a) through h) below be the same as that used for the B t, crawispace, or enclosure floor) ral member (V Zones only) ment servicing the building on in Comments) o building (LAG) to building (HAG) tion of deck or stairs, including I D – SURVEYOR, ENGINEER, a land surveyor, engineer, or archite Certificate represents my best effor nishable by fine or imprisonment in	CORMATION (SURVE Building Under Construct g is complete. RR, AR/A, AR/AE, AR/A1 to Rico only, enter meter tical Datum: V. NGVD 1929 IN FE. OR ARCHITECT CE ect authorized by law to rts to interpret the data Orace 18 U.S. Code. Section Construction of the data Section of the data Section Construction of the data Section Section of the data Section of the data Sec	EY REQUIRI ction* L-A30, AR/AH ers. VAVD 1988 Check the me feet fee	
 C1. Building elevations ar *A new Elevation Ceri C2. Elevations – Zones A: C2.a-h below accordi Benchmark Utilized:	SECTION C e based on: lificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the eleving ng elevations must b r (including basement gher floor ast horizontal structur op of slab) of machinery or equip equipment and location inished) grade next to finished) grade next to finished) grade next to section SECTION gned and sealed by a e information on this statement may be pur are provided on back	A BUILDING ELEVATION INF Construction Drawings* d when construction of the buildin h BFE), VE, V1–V30, V (with BFE), A gram specified in Item A7. In Puer Ver ations in items a) through h) below be the same as that used for the B t, crawlspace, or enclosure floor) ral member (V Zones only) ment servicing the building on in Comments) o building (LAG) to building (HAG) ion of deck or stairs, including I D – SURVEYOR, ENGINEER, aland surveyor, engineer, or archite Certificate represents my best effor nishable by fine or imprisonment ur k of form. Were latitude and h	CORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter meter tical Datum: COMPACTION (SURVE) FE. COMPACTION (SURVE) COMPACTION (SUR	EY REQUIRI ction* L-A30, AR/AH ers. VAVD 1988 Check the me feet fee	
 C1. Building elevations ar *A new Elevation Ceri C2. Elevations – Zones A: C2.a–h below accordi Benchmark Utilized:	SECTION C e based on: Lificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the eleval ng elevations must b r (including basement gher floor ast horizontal structur op of slab) of machinery or equip equipment and location inished) grade next to finished) grade next to finished) grade next to finished) grade next to sECTION gned and sealed by a e information on this statement may be pur are provided on back ts.	A BUILDING ELEVATION INF Construction Drawings* d when construction of the buildin h BFE), VE, V1–V30, V (with BFE), A gram specified in Item A7. In Puer	CORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter meter tical Datum: CORDANIES (CORDEN) FE. CORDANIES (CORDEN) CORDANIES (CORD	EY REQUIRI ction* L-A30, AR/AH ers. VAVD 1988 Check the me feet fourtified f	
C1. Building elevations ar *A new Elevation Cert C2. Elevations – Zones A: C2.a–h below accordi Benchmark Utilized: Indicate elevation dat Datum used for buildi a) Top of bottom floo b) Top of the next hig c) Bottom of the low d) Attached garage (t e) Lowest adjacent (f g) Highest adjacent (f g) Highest adjacent (f h) Lowest adjacent (f g) Highest adjacent (f h) Lowest adjacent (f c) Structural support	SECTION C e based on: Lificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the elevi- ng elevations must b r (including basement gher floor east horizontal structur op of slab) of machinery or equip equipment and locatio inished) grade next to finished) grade next to finished) grade next to finished) grade next to section gned and sealed by a e information on this statement may be pur are provided on back ts.	A BUILDING ELEVATION INF Construction Drawings* d when construction of the buildin h BFE), VE, V1–V30, V (with BFE), A gram specified in Item A7. In Puer	CORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter meter (cal Datum: 	EY REQUIRI ction* L-A30, AR/AH rrs. VAVD 1988 Check the me Check the m	
C1. Building elevations ar *A new Elevation Cert C2. Elevations – Zones A: C2.a–h below accordi Benchmark Utilized:	SECTION C e based on: Lificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the elevi- ng elevations must b r (including basement gher floor ast horizontal structur op of slab) of machinery or equip equipment and locatio inished) grade next to finished) grade next to finished) grade next to section section on this statement may be pur are provided on back ts.	Company Name	ORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter meter tical Datum: 	EY REQUIRI ction* L-A30, AR/AH ers. VAVD 1988 Check the me Check the me	
C1. Building elevations ar *A new Elevation Ceri C2. Elevations – Zones A: C2.a–h below accordi Benchmark Utilized:	SECTION C e based on: lificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the eleva ng elevations must b r (including basement gher floor ast horizontal structur op of slab) of machinery or equip equipment and locatio inished) grade next t finished) grade next t finished) grade next t section section on this statement may be pur are provided on back ts.	Company Name Company Name		EY REQUIRI ction* L-A30, AR/AH ers. VAVD 1988 Check the me Check the me	
C1. Building elevations ar *A new Elevation Ceri C2. Elevations – Zones A: C2.a–h below accordi Benchmark Utilized:_ Indicate elevation dat Datum used for buildi a) Top of bottom floo b) Top of the next hig c) Bottom of the low d) Attached garage (1 e) Lowest elevation d (Describe type of d f) Lowest adjacent (1 g) Highest adjacent (1 g) Highest adjacent (1 h) Lowest adjacent (2 g) Highest adjacent (2 h) Lowest adjacent (3 c) Check here if comments Check here if comments Check here if attachmen Certifier's Name Title Address	SECTION C e based on: Lificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the elev- ing elevations must b r (including basement ther floor) est horizontal structur op of slab) of machinery or equip equipment and locatio inished) grade next t finished) grade next t finished) grade next t section statement may be pur are provided on back ts.	Company Name Company Name Company Name Company Name City	CORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Rico only, enter meter (tical Datum) V. D NGVD 1929 IN FE. OR ARCHITECT CE A COR ARCHITECT CE	EY REQUIRI ction* L-A30, AR/AH ers. VAVD 1988 Check the me Check the me	
C1. Building elevations ar *A new Elevation Ceri C2. Elevations – Zones A: C2.a–h below accordi Benchmark Utilized:_ Indicate elevation dat Datum used for buildi a) Top of bottom floo b) Top of the next hig c) Bottom of the low d) Attached garage (t e) Lowest elevation d (Describe type of d f) Lowest adjacent (f g) Hignest adjacent (f h) Lowest adjacent (f h) Lowest adjacent (f c) Hignest adjacent (f h) Lowest adjacent (f c) Check here if comments Check here if comments Check here if attachment Certifier's Name Title Address Signature	SECTION C e based on: lificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the elev- ng elevations must b r (including basement gher floor ast horizontal structur op of slab)) of machinery or equip aquipment and locatit inished) grade next to finished) grade next to finished) grade next to statement may be pur are provided on back ts.	Company Name Company Name Company Name Company Name Company Name Company Name	CORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Ricc only, enter meter (tical Datum) V. D NGVD 1929 IN FE. 	EY REQUIRI ction* [L-A30, AR/AH ers. VAVD 1988 [Check the me feet feet feet feet feet feet feet fe	
C1. Building elevations ar *A new Elevation Ceri C2. Elevations – Zones A: C2.a–h below accordi Benchmark Utilized:_ Indicate elevation dat Datum used for buildi a) Top of bottom floo b) Top of the next hig c) Bottom of the low d) Attached garage (f e) Lowest elevation of (Describe type of a f) Lowest adjacent (f g) Highest adjacent (f g) Highest adjacent (f h) Lowest adjacent (f h) Lowest adjacent (f g) Highest adjacent (f h) Lowest adjacent (f h) Lowest adjacent (f g) Highest adjacent (f h) Lowest (SECTION C e based on: lificate will be require L-A30, AE, AH, A (with ng to the building dia um used for the eleva ng elevations must b r (including basement gher floor ast horizontal structur op of slab)) of machinery or equip aquipment and locatic inished) grade next to finished) grade next to finished) grade next to section statement may be pur are provided on back ts.	BUILDING ELEVATION INF Comstruction Drawings* di when construction of the buildin h BFE), VE, V1–V30, V (with BFE), A gram specified in Item A7. In Puer	CORMATION (SURVE Building Under Construct g is complete. AR, AR/A, AR/AE, AR/A1 to Ricc only, enter meter (cal Datum:) V. D NGVD 1929 IN FE. 	EY REQUIRI ction* [L-A30, AR/AH ers. VAVD 1988 [Check the me feet feet feet feet feet feet feet fe	

IMPORTANT: In these spaces, copy the corresponding information from Section A.					FC	FOR INSURANCE COMPANY USE	
Building Str	reet Address (including Apt., Unit, S	Suite, and/or Bldg. No.) or PO.	Route and Box No.		Po	licy Number:	
City		State	ZIP Code		Co	mpany NAIC Numb	per:
	SECTION D - S	URVEYOR, ENGINEER, O	R ARCHITECT CE	RTIFICAT	ION (CON	TINUED)	
Copy both s	sides of this Elevation Certificate for	or (1) community official, (2) in	surance agent/comp	any, and (3) building ow	ner.	
Comments	From Section C2(e) wj	hat is the machinery or e	equipment and o	r other c	omments		
Signature	M .1 . 1 . 1.1.		Date				
Signature	Must be signed and dated						
SECT	ION E - BUILDING ELEVATIO	N INFORMATION (SURVE	Y NOT REQUIRED) FOR ZO	DNE AO AN	D ZONE A (V	VITHOUT BFE)
For Zones A For Items E1	O and A (without BFE), complete It 1–E4, use natural grade, if available	ems E1–E5. If the Certificate i e. Check the measurement us	is intended to suppor sed. In Puerto Rico or	rt a LOMA o nly, enter m	or LOMR-F re- neters.	quest, complete	Sections A, B, and C.
1. Provide	elevation information for the follow	ving and check the appropriate	e boxes to show whet	ther the ele	evation is abo	ove or below the	highest adjacent
grade (H	HAG) and the lowest adjacent grade	e (LAG).		□ faat	Dimeter	D about an	below the UAC
b) Top o	of bottom floor (including basement	, crawlspace, or enclosure) is		feet	meters	above or	below the LAG.
2. For Build	ding Diagrams 6–9 with permanen	t flood openings provided in Si	ection A Items 8 and,	/or 9 (see	pages 8-9 o	f Instructions),	
the next	t higher floor (elevation C2.b in the	diagrams) of the building is		🗌 feet	meters	above or	below the HAG.
3. Attached	d garage (top of slab) is			☐ feet	meters	above or	below the HAG.
E4. Top of p	blatform of machinery and/or equip	ment servicing the building is	tom floor electricit	☐ feet		above or	below the HAG.
ordinance	ce? Yes No Unknow	n. The local official must certif	y this information in	Section G.	e with the co	mmunity's flood	plain management
	SECTION F - P	ROPERTY OWNER (OR O	WNER'S REPRES	ENTATIV	E) CERTIFI	CATION	
The property	y owner or owner's authorized repr	esentative who completes Sec	ctions A, B, and E for	Zone A (wi	thout a FEMA	A-issued or com	munity-issued BFE) or
Zone AO mu	ust sign here. The statements in S	ections A, B, and E are correct	t to the best of my kr	nowledge.			
Property Ow	wher or Owner's Authorized Represe	Complet	te Section F	if no	BFE and	Section 1	I is used
Address			City		State	ZIP Co	de
Signature			Date		Teleph	one	
Comments							
							· · · · · · · · · · · · · · · · · · ·
						Check	here if attachments.
		SECTION G - COMMUNI	TY INFORMATION	(OPTION	NAL)		
The local off	ficial who is authorized by law or or evation Certificate. Complete the an	dinance to administer the comm plicable item(s) and sign below	nunity's floodplain ma	nagement o	ordinance can	complete Section	ons A, B, C (or E), and
G1. 🗌 The	e information in Section C was tal	ken from other documentation	n that has been sign	ed and sea	aled by a licer	nsed survevor.	engineer, or architect
wh	to is authorized by law to certify el	evation information. (Indicate	the source and date	e of the ele	evation data i	n the Comment	s area below.)
G2. ∐ A C G3. □ Th	e following information (Items G4-	-G9) is provided for communi	cone A (without a FEN	MA-Issued o	or community	-issued BFE) or	Zone AO.
G4. Permit	t Number	G5. Date Permit Issued	G6.	Date Cert	ificate Of Con	noliance/Occup	ancy Issued
C7 This p	armit has been issued for:		tantial Improvement				
G8. Elevati	tion of as-built lowest floor (includir	ig basement) of the building:		feet	meters	Datum	
G9. BFE or	r (in Zone AO) depth of flooding at	the building site:		🗆 feet	meters	Datum	
G10.Comm	nunity's design flood elevation:			□ feet	meters	Datum	
Local Officia	al's Name If G1,G2,G8 on	G9 are checked	Title				
Community	Name		Telephone				
Signature			Date				
Comments							
Comments							
Comments		1				Check	here if attachmente

For	Sec	tion	A6

ELEVATION CERTIFICATE, page 4

BUILDING PHOTOGRAPHS
Continuation Page

IMPORTANT: In these spaces, copy t	FOR INSURANCE COMPANY USE		
Building Street Address (including Apt	Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or PO. Route and Box No.		
City	State ZIP Code	Company NAIC Number:	

If submitting more photographs than will fit on the preceding page, affix the additional photographs below. Identify all photographs with: date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View." When applicable, photographs must show the foundation with representative examples of the flood openings or vents, as indicated in Section A8.

FEMA Form 086-0-33 (Revised 7/12)

Replaces all previous editions.

Building Diagrams

The following diagrams illustrate various types of buildings. Compare the features of the building being certified with the features shown in the diagrams and select the diagram most applicable. Enter the diagram number in Item A7, the square footage of crawlspace or enclosure(s) and the area of flood openings in square inches in Items A9.a-c, and the elevations in Items C2.a-h.

In A zones, the floor elevation is taken at the top finished surface of the floor indicated; in V zones, the floor elevation is taken at the bottom of the lowest horizontal structural member (see drawing in instructions for Section C).

All split-level buildings that are slab-on-grade, either detached or row type (e.g., townhouses); with or without attached garage.

DIAGRAM 5

All buildings elevated on piers, posts, piles, columns, or parallel shear walls. No obstructions below the elevated floor.

Distinguishing Feature – For all zones, the area below the elevated floor is open, with no obstruction to flow of floodwaters (open lattice work and/or insect screening is permissible).

DIAGRAM 4

DIAGRAM 6

All buildings elevated on piers, posts, piles, columns, or parallel shear walls with full or partial enclosure below the elevated floor.

Distinguishing Feature – For all zones, the area below the elevated floor is enclosed, either partially or fully. In A Zones, the partially or fully enclosed area below the elevated floor is with or without openings** present in the walls of the enclosure. Indicate information about enclosure size and openings in Section A – Property Information.

* A floor that is below ground level (grade) on all sides is considered a basement even if the floor is used for living purposes, or as an office, garage, workshop, etc.

** An "opening" is a permanent opening that allows for the free passage of water automatically in both directions without human intervention. Under the NFIP, a minimum of 2 openings is required for enclosures or crawlspaces. The openings shall provide a total net area of not less than 1 square inch for every square foot of area enclosed, excluding any bars, louvers, or other covers of the opening. Alternatively, an Individual Engineered Flood Openings Certification or an Evaluation Report issued by the International Code Council Evaluation Service (ICC ES) must be submitted to document that the design of the openings will allow for the automatic equalization of hydrostatic flood forces on exterior walls. A window, a door, or a garage door is not considered an opening; openings may be installed in doors. Openings shall be on at least 2 sides of the enclosed area. If a building has more than 1 enclosed area, each area must have openings to allow floodwater to directly enter. The bottom of the openings must be no higher than 1.0 foot above the higher of the exterior or interior grade or floor immediately below the opening. For more guidance on openings, see NFIP Technical Bulletin 1.

NFIP Elevation Certificate Instructions - Page 8

DIAGRAM 7

All buildings elevated on full-story foundation walls with a partially or fully enclosed area below the elevated floor. This includes walkout levels, where at least 1 side is at or above grade. The principal use of this building is located in the elevated floors of the building.

Distinguishing Feature – For all zones, the area below the elevated floor is enclosed, either partially or fully. In A Zones, the partially or fully enclosed area below the elevated floor is with or without openings** present in the walls of the enclosure. Indicate information about enclosure size and openings in Section A – Property Information.

DIAGRAM 8

All buildings elevated on a crawlspace with the floor of the crawlspace at or above grade on at least 1 side, with or without an attached garage.

Distinguishing Feature – For all zones, the area below the first floor is enclosed by solid or partial perimeter walls. In all A zones, the crawlspace is with or without openings** present in the walls of the crawlspace. Indicate information about crawlspace size and openings in Section A – Property Information.

DIAGRAM 9

Distinguishing Feature – The bottom (crawlspace) floor is below ground level (grade) on all sides.* (If the distance from the crawlspace floor to the top of the next higher floor is more than 5 feet, or the crawlspace floor is more than 2 feet below the grade [LAG] on all sides, use Diagram 2.)

* A floor that is below ground level (grade) on all sides is considered a basement even if the floor is used for living purposes, or as an office, garage, workshop, etc.

** An "opening" is a permanent opening that allows for the free passage of water automatically in both directions without human intervention. Under the NFIP, a minimum of 2 openings is required for enclosures or crawlspaces. The openings shall provide a total net area of not less than 1 square inch for every square foot of area enclosed, excluding any bars, louvers, or other covers of the opening. Alternatively, an Individual Engineered Flood Openings Certification or an Evaluation Report issued by the International Code Council Evaluation Service (ICC ES) must be submitted to document that the design of the openings will allow for the automatic equalization of hydrostatic flood forces on exterior walls. A window, a door, or a garage door is not considered an opening; openings may be installed in doors. Openings shall be on at least 2 sides of the enclosed area. If a building has more than 1 enclosed area, each area must have openings to allow floodwater to directly enter. The bottom of the openings must be no higher than 1.0 foot above the higher of the exterior or interior grade or floor immediately below the opening. For more guidance on openings, see NFIP Technical Bulletin 1.

NFIP Elevation Certificate Instructions - Page 9

CITY OF ST. MARYS 418 OSBORNE STREET ST. MARYS, GEORGIA 31558 PLANNING AND ZONING DEPARTMENT TELEPHONE: 912-510-4032 FAX: 912-510-4014

June 3, 2015

Name Address St. Marys, GA 31558

Dear Property Owner:

You have received this letter because your property is in an area that has been flooded several times. Our community is concerned about repetitive flooding and has an active program to help you protect yourself and your property from future flooding, but here are some things you can do:

- Check with the Planning Department on the extent of past flooding in your area. Department staff can tell you about the causes of repetitive flooding, what the City is doing about it, and what would be an appropriate flood protection level. The staff can visit your property to discuss flood protection alternatives.
- 2. Prepare for flooding by doing the following:
 - Know how to shut off the electricity and gas to your house when a flood comes.
 - Make a list of emergency numbers and identify a safe place to go.
 - Make a household inventory, especially of basement contents.
 - Put insurance policies, valuable papers, medicine, etc., in a safe place.
 - Collect and put cleaning supplies, camera, waterproof boots, etc., in a handy place.
 - Develop a disaster response plan. See the Red Cross's website at www.redcross.org for information about preparing your home and family for a disaster.
 - Get a copy of *Repairing Your Flooded Home*. We have copies at the Planning Department or it can be found on the Red Cross' website, too.
- 3. Consider some permanent flood protection measures.
 - Mark your fuse or breaker box to show the circuits to the floodable areas. Turning off the power to the basement before a flood can reduce property damage and save lives.
 - Consider elevating your house above flood levels.

(Continued on the next page)

- Check your building for water entry points, such as basement windows, the basement stairwell, doors, and dryer vents. These can be protected with low walls or temporary shields.
- Install a floor drain plug, standpipe, overhead sewer, or sewer backup valve to prevent sewer backup flooding.
- More information can be found at FEMA's website, www.ready.gov/floods.
- Note that some flood protection measures may need a building permit and others may not be safe for your type of building, so be sure to talk to the Building Department.
- 4. Talk to the Planning Department for information on financial assistance.
 - If you are interested in elevating your building above the flood level, we may apply for Federal Grant to cover some of the cost.
 - Get a flood insurance policy it will help pay for repairs after a flood and, in some cases, it
 will help pay the costs of elevating a substantially damaged building.
- 5. Get a flood insurance policy.
 - Homeowner's insurance policies do not cover damage from floods. However, because our community participates in the National Flood Insurance Program, you can purchase a separate flood insurance policy. This insurance is backed by the Federal government and is available to everyone, even properties that have been flooded. Because our community participates in the Community Rating System, you will receive a reduction in the insurance premium.
 - Some people have purchased flood insurance because it was required by the bank when they got a mortgage or home improvement loan. Usually these policies just cover the building's structure and not the contents. During the kind of flooding that happens in your area, there is usually more damage to the furniture and contents than there is to the structure. Be sure you have contents coverage.
 - Don't wait for the next flood to buy insurance protection. In most cases, there is a 30-day waiting period before National Flood Insurance Program coverage takes effect.
 - Contact your insurance agent for more information on rates and coverage.

If you should have any questions, please do not hesitate to contact me at (912) 510-4025.

Sincerely,

Michele Wood, CFM Floodplain Manager City of St. Marys Many people have made invaluable contributions to this project over the past several years, and this is our best attempt to acknowledge the time and effort of individuals and groups. However, we do recognize in advance that this list is almost certainly incomplete and apologize in advance for unintended omissions. Please also note that acknowledged individuals bear no responsibility for the contents in the report, which is the sole responsibility of the authors.

We thank the staff, elected officials, and local citizens in the City of St. Marys for their participation in — and patience with — this project. Special thanks go to each of the following staff members for their engagement and assistance throughout the project period: Roger Weaver (former Planning Director, now retired) for his overall enthusiasm and in-depth conversations about the history of St. Marys and the importance of floodplain management; Michele Wood (Assistant Planner and Floodplain Manager) for her many hours of collaboration with the project team in working through floodplain regulations and Community Rating System materials; Dr. Jeff Adams (Community Development Director) for the energy and insights he brought to this project when he joined the City, and his continued persistence in making monthly updates and serving as the primary project's liaison to the City Council; Bobby Marr (Public Works Director) for his eager assistance in locating digital and print datasets, as well as his very detailed observations and insights about local infrastructure; John Holman (City Manager) for his facilitation of public meetings and overall leadership; and Becky Myers (Main Street Coordinator) for her efforts and assistance to link this flood resiliency project with downtown visioning. Current and past members of the City's Historic Preservation Commission also provided valued input that helped guide the project.

We give very special thanks to the St. Marys EarthKeepers and, in particular, the organization Chair, Alex Kearns. The genesis of this project can be directly credited to the efforts of Ms. Kearns and the St. Marys EarthKeepers to host a local sea-level rise forum in February 2013. The St. Marys EarthKeepers provided many hours of volunteer assistance to the research team over the course of the project, all of which proved vital to the project delivery and completion. A variety of faculty and staff at the University of Georgia provided key contributions to the outreach components and development of further research ideas over the course of this project. These include J. Scott Pippin, Shana Jones, Daniel Bivins, Leigh Elkins, Langford Holbrook, Mathew Hauer, and Jimmy Nolan from UGA Carl Vinson Institute of Government; Jessica Brown, Keren Giovengo, and L. Mark Risse from UGA Marine Extension and Georgia Sea Grant; and Jon Calabria, Alfie Vick, Rosanna Rivero, and Alison Smith from UGA College of Environment and Design.

Several undergraduate students from Stetson University provided assistance with development of GIS analyses, graphic design, and community outreach over the course of this project. These include Justin Baumann (Class of 2016), Emily Niederman (Class of 2017), and George Winsten (Class of 2018). All students who took Stetson's Geographic Information Systems and Science course (ENSS 301) in the fall 2015 and fall 2016 semesters also had opportunities to assist with the analysis of data from St. Marys.

Other individuals and institutions that provided support and/or information critical to the final project include: Lupita McClenning and David Dantzler (Coastal Regional Commission of Georgia); Jennifer Kline (Coastal Resources Division, Georgia Department of Natural Resources); and the Camden County Tax Assessor's Office. We give extra special thanks to Courtney Reich of the Ecological Planning Group, LLC, for technical comments, feedback, and outreach support that were critical for helping to ensure that the final document provides information that will be most beneficial to proactive floodplain management and planning activities in St. Marys over the long-term.

This publication was supported and made possible in part by an Institutional Grant (NA100AR4170098) to the Georgia Sea Grant College Program from the National Sea Grant Office, National Oceanic and Atmospheric Administration, U.S. Department of Commerce. All views, opinions, findings, conclusions, and recommendations expressed in this material are those of the authors and do not necessarily reflect the opinions of the Georgia Sea Grant College Program or the National Oceanic and Atmospheric Administration.

GRAPHIC & PUBLICATION DESIGN BY JULIE SPIVEY, ASSOCIATE PROFESSOR OF ART/GRAPHIC DESIGN AT THE UNIVERSITY OF GEORGIA WITH ASSISTANCE FROM NICOLE KIM, BFA '17.
Publication supported in part by an Institutional Grant (NA13OAR4170151) to the Georgia Sea Grant College Program from the National Sea Grant Office, National Oceanic and Atmospheric Administration, U.S. Department of Commerce. All views, opinions, findings, conclusions, and recommendations expressed in this material are those of the author(s) and do not necessarily reflect the opinions of the Georgia Sea Grant College Program or the National Oceanic and Atmospheric Administration.

